

# SAFETY DATA SHEET

### 1. Identification

1. Identification			
Product identifier	LPS® Instant Super Degreaser		
Other means of identification			
Part Number	00720		
Recommended use	A nonflammable, heavy-duty solvent designed to remove oil, grease, wax, dirt, moisture, tar and other contaminants.		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/	Distributor information		
Manufacturer			
Manufacturer			
Company name	ITW Pro Brands		
Address	4647 Hugh Howell Rd.		
	Tucker, GA 30084		
Country	(U.S.A.)		
	Tel: +1 770-243-8800		
In Case of Emergency	1-800-424-9300 (inside U.S.)		
	+001 703-527-3887 (outside U.S.)		
Website	www.lpslabs.com		
E-mail	lpssds@itwprobrands.com		
2. Hazard(s) identification			
Physical hazards	Gases under pressure	Compressed gas	
Health hazards	Skin corrosion/irritation	Category 2	
	Serious eye damage/eye irritation	Category 2A	
	Carcinogenicity	Category 2	
	Reproductive toxicity	Category 1B	
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation	
	Specific target organ toxicity, single exposure	Category 3 narcotic effects	
	Specific target organ toxicity, repeated exposure	Category 2 (Central Nervous System, Liver)	
Environmental hazards	Not classified.		
OSHA defined hazards	Not classified.		
Label elements			

Signal word Hazard statement

Causes serious eye irritation. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May damage fertility or the unborn child. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs (Central Nervous System, Liver) through prolonged or repeated exposure.

Precautionary statement Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Danger

Response	If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.	
Storage	Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None known.	

# 3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
n-Propyl Bromide		106-94-5	90 - 100
Carbon Dioxide		124-38-9	1 - 5
1,2 Butylene Oxide		106-88-7	< 1

### 4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Not likely, due to the form of the product. Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.
5. Fire-fighting measures	
Suitable extinguishing media	Water spray. Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Cool containers exposed to flames with water until well after the fire is out.
General fire hazards	Contents under pressure. Pressurized container may explode when exposed to heat or flame.

### 6. Accidental release measures

o. Accidental release measures				
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.			
Methods and materials for containment and cleaning up	Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. This product is miscible in water.			
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.			
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.			
	Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.			
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.			
7. Handling and storage				
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.			
Conditions for safe storage,	Level 1 Aerosol.			
including any incompatibilities	Store locked up. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).			

# 8. Exposure controls/personal protection

Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
,	TWA	5000 ppm	
n-Propyl Bromide (CAS 106-94-5)	TWA	0.1 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	

Components	Туре	Value	
		5000 ppm	
US. Workplace Environme	ental Exposure Level (WEEL) Guides		
Components	Туре	Value	
1,2 Butylene Oxide (CAS 106-88-7)	TWA	5.9 mg/m3	
		2 ppm	
iological limit values	No biological exposure limits noted f	for the ingredient(s).	
xposure guidelines			
US - California OELs: Skin	designation		
n-Propyl Bromide (CAS	106-94-5) Can	be absorbed through the skin.	
ppropriate engineering ontrols	should be matched to conditions. If a or other engineering controls to main exposure limits have not been estab	0 air changes per hour) should be used. Ventilation rates applicable, use process enclosures, local exhaust ventilation ntain airborne levels below recommended exposure limits. It plished, maintain airborne levels to an acceptable level. Eye ver must be available when handling this product.	
ndividual protection measure	s, such as personal protective equipr		
Eye/face protection	Wear safety glasses with side shield	ds (or goggles).	
Skin protection			
Hand protection	Wear appropriate chemical resistant supplier.	t gloves. Suitable gloves can be recommended by the glove	
Other	Wear appropriate chemical resistant	t clothing. Use of an impervious apron is recommended.	
Respiratory protection	In case of insufficient ventilation, we	ear suitable respiratory equipment.	
Thermal hazards	Wear appropriate thermal protective	e clothing, when necessary.	
eneral hygiene	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		

### 9. Physical and chemical properties

Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Colourless to light yellow.
Odor	Strong.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	-166 °F (-110 °C) (estimated based on nPB)
Initial boiling point and boiling range	158 °F (70 °C)
Flash point	None. ASTM D-56 TCC (Liquid portion)
Evaporation rate	4.7
Flammability (solid, gas)	Non flammable gas.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	3.8 %
Flammability limit - upper (%)	9.5 %
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	134 mm Hg @ 25°C
Vapor density	4.24 (estimated based on nPB)
Relative density	Not available.

Solubility(ies)		
Solubility (water)	0.24 g/ml @ 25°C (estimated based on nPB)	
Partition coefficient (n-octanol/water)	Not available.	
Auto-ignition temperature	> 914 °F (> 490 °C) (estimated based on nPB)	
Decomposition temperature	Not available.	
Viscosity	Not available.	
Other information		
Explosive properties	Not explosive.	
Heat of combustion	16 kJ/g (estimated based on nPB)	
Oxidizing properties	Not oxidizing.	
Percent volatile	100 %	
Specific gravity	1.34 - 1.36	
VOC	96.5 % per US State and Federal Consumer Product Regulations	

## 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides. Hydrogen bromide.

# 11. Toxicological information

#### Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory system.		
Skin contact	Causes skin irritation.		
Eye contact	Causes serious eye irritation.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.		
Information on toute dealers and all			

#### Information on toxicological effects

Acute toxicity

Narcotic effects. May cause respiratory irritation.

Components	Species	Test Results
1,2 Butylene Oxide (CAS 106-8	8-7)	
Acute		
Dermal		
LD50	Rabbit	1.77 ml/kg, 24 Hours
<b>Inhalation</b> <i>Vapor</i> LC50	Rat	> 6.3 mg/l, 4 Hours
	Παι	> 6.5 mg/i, 4 Hours
<b>Oral</b> LD50	Rat	1100 µl/kg
n-Propyl Bromide (CAS 106-94-	5)	
<u>Acute</u>		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours

Components	Species	Test Results
Oral		
LD50	Rat	> 2000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected t	o cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
ACGIH Carcinogens		
n-Propyl Bromide (CAS 1	06-94-5)	A3 Confirmed animal carcinogen with unknown relevance to humans.
IARC Monographs. Overall	Evaluation of Carcinogenicity	
1,2 Butylene Oxide (CAS n-Propyl Bromide (CAS 1 OSHA Specifically Regulate		2B Possibly carcinogenic to humans. 2B Possibly carcinogenic to humans. 001-1050)
Not regulated.	ogram (NTP) Report on Carcin	oriens
n-Propyl Bromide (CAS 1		Reasonably Anticipated to be a Human Carcinogen.
Reproductive toxicity	May damage fertility or the unborn child.	
Specific target organ toxicity - single exposure	May cause respiratory irritation. May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	
12. Ecological information	ı	
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment	
Components	Species	Test Results
n-Propyl Bromide (CAS 106-9	94-5)	
<b>Aquatic</b> Fish	LC50 Fathead minne	ow (Pimephales promelas) 67.3 mg/l, 96 hours
* Estimates for product may b	e based on additional compone	nt data not shown.
Persistence and degradability	No data is available on the de	
Bioaccumulative potential		
Partition coefficient n-octar n-Propyl Bromide	ol / water (log Kow)	2.1
Mobility in soil	No data available.	
Other adverse effects	None known.	
13. Disposal consideration	ns	
Disposal instructions	Contents under pressure. Do not puncture, incinerate or crush. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with a	II applicable regulations.
Hazardous waste code	The waste code should be as disposal company.	signed in discussion between the user, the producer and the waste

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, non flammable
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not available.
	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name	Aerosols, non flammable
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not available.
Environmental hazards	No.
ERG Code	
	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	Allowed with restrictions.
Cargo aircraft only IMDG	Allowed with restrictions.
	UN1950
UN number	AEROSOLS, non flammable
UN proper shipping name Transport hazard class(es)	AEROSOLS, NOI Hammable
Class	2.2
	2.2
Subsidiary risk Label(s)	2.2
Packing group	Not available.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
-	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not available.
Annex II of MARPOL 73/78 and	
the IBC Code	
DOT	





# 15. Regulatory information

15. negulatory information				
US federal regulations	This product is a "Haz Standard, 29 CFR 19		efined by the OSHA Hazard Communication	1
TSCA Section 12(b) Expor	t Notification (40 CFR 70	07, Subpt. D)		
Not regulated.				
CERCLA Hazardous Subs	•	4)		
1,2 Butylene Oxide (CA SARA 304 Emergency rele		Listed.		
Not regulated. OSHA Specifically Regula	ted Substances (29 CFR	1910.1001-1050)		
Not regulated.				
Superfund Amendments and F	Reauthorization Act of 1	986 (SARA)		
Hazard categories	Immediate Hazard - Y Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - Ye Reactivity Hazard - No	Yes S		
SARA 302 Extremely haza	rdous substance			
Not listed.				
SARA 311/312 Hazardous chemical	Yes			
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
1,2-BUTYLENE OXIDE		106-88-7	< 1	
Other federal regulations				
Clean Air Act (CAA) Section	on 112 Hazardous Air Po	ollutants (HAPs) List		
1,2 Butylene Oxide (CA Clean Air Act (CAA) Section		ease Prevention (40 C	FR 68.130)	
Not regulated.				
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations				
US - California Proposition	n 65 - CRT: Listed date/(	Carcinogenic substand	ce	
n-Propyl Bromide (CAS		Listed: Augus		
US - California Proposition				
n-Propyl Bromide (CAS US - California Proposition		Listed: Decen Female reproductive to		
n-Propyl Bromide (CAS	106-94-5)	Listed: Decen	nber 7, 2004	
US - California Proposition	1 65 - CRT: Listed date/	Male reproductive toxi	n	
n-Propyl Bromide (CAS		Listed: Decen		
US. California. Candidate (a))	Chemicals List. Safer Co	onsumer Products Re	gulations (Cal. Code Regs, tit. 22, 69502.3	3, subd.
1,2 Butylene Oxide (CA n-Propyl Bromide (CAS				

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

Issue date Revision date Version #	05-06-2016 12-29-2016 02
Disclaimer	ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.