

# SAFETY DATA SHEET

#### 1. Identification

Product identifier	LPS® CFC Free		
Other means of identification			
Part Number	03101, 03105, 03155		
Recommended use	A fast drying industrial cleaning solvent designed to remove soil and other contaminants.		
<b>Recommended restrictions</b>	None known.		
Manufacturer/Importer/Supplie	r/Distributor information		
Manufacturer			
Manufacturer			
Company name	ITW Pro Brands		
Address	4647 Hugh Howell Rd.		
	Tucker, GA 30084		
Country	(U.S.A.)		
	Tel: +1 770-243-8800		
In Case of Emergency	1-800-424-9300 (inside U.S.)		
	+001 703-527-3887 (outside U.S.)		
Website	www.lpslabs.com		
E-mail	lpssds@itwprobrands.com		
2. Hazard(s) identification	1		
Physical hazards	Flammable liquids	Category 2	
Health hazards	Skin corrosion/irritation	Category 2	
	Serious eye damage/eye irritation	Category 2A	
	Reproductive toxicity (fertility)	Category 2	
	Specific target organ toxicity, single exposure	Category 3 narcotic effects	
	Aspiration hazard	Category 1	
Environmental hazards	Not classified.		
OSHA defined hazards	Not classified.		
Label elements			
	$\land \land \land \land$		



Signal word Hazard statement

Precautionary statement Prevention Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection.

Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.
Storage	Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None known.

# 3. Composition/information on ingredients

**Mixtures** 

Chemical name	Common name and synonyms	CAS number	%
2-Methylpentane		107-83-5	70 - 80
Isopropanol		67-63-0	10 - 20
Pentane		109-66-0	5 - 10
N-Hexane		110-54-3	0.1 - 1

### 4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent entry into waterways, sewer, basements or confined areas.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Should be handled in closed systems, if possible. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact during pregnancy/while nursing. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### **Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Isopropanol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
N-Hexane (CAS 110-54-3)	PEL	1800 mg/m3	
		500 ppm	
Pentane (CAS 109-66-0)	PEL	2950 mg/m3	
		1000 ppm	
<b>US. ACGIH Threshold Limit Values</b>			
Components	Turno	Value	
componento	Туре	value	
2-Methylpentane (CAS 107-83-5)	STEL	1000 ppm	
2-Methylpentane (CAS			
2-Methylpentane (CAS	STEL	1000 ppm	
2-Methylpentane (CAS 107-83-5)	STEL	1000 ppm 500 ppm	
2-Methylpentane (CAS 107-83-5)	STEL TWA STEL	1000 ppm 500 ppm 400 ppm	

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Тур	e	Va	alue
Isopropanol (CAS 67-63-0)	STE	iL		25 mg/m3
				0 ppm
	TW	4		30 mg/m3
N Hovana (CAS 110 54 9)	TW	^		0 ppm 30 mg/m3
N-Hexane (CAS 110-54-3)	1 007	ч		) ppm
Pentane (CAS 109-66-0)	Ceil	ina		00 mg/m3
				0 ppm
	TW	٩		50 mg/m3
			12	20 ppm
ological limit values				
ACGIH Biological Exposur	e Indices			
Components	Value	Determinant	Specimen	Sampling Time
Isopropanol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
N-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio	Urine	*
		n, without hydrolysis		
* - For sampling details, plea	ase see the source do			
posure guidelines US - California OELs: Skin	designation			
	-	Conto	abcarbad three	igh the skip
N-Hexane (CAS 110-54 US ACGIH Threshold Limit			absorbed throu	ıyıı me skin.
N-Hexane (CAS 110-54	-3)	Can be	absorbed throu	ugh the skin.
propriate engineering ntrols	changes per hour) applicable, use pro maintain airborne established, maint	should be used. Ve ocess enclosures, lo levels below recomm	ntilation rates sl cal exhaust ven nended exposur o an acceptable	Good general ventilation (typically 10 air hould be matched to conditions. If tilation, or other engineering controls to re limits. If exposure limits have not been level. Provide eyewash station. Eye was
dividual protection measures				
Eye/face protection		es with side shields		
Skin protection				
Hand protection	Wear appropriate	chemical resistant g	oves.	
Other	Wear appropriate	chemical resistant of	othina	
Respiratory protection	If engineering cont limits (where appli	Wear appropriate chemical resistant clothing. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.		
Thermal hazards	,,	thermal protective cl		
eneral hygiene nsiderations	When using do no after handling the	t smoke. Always obs	erve good pers eating, drinking	onal hygiene measures, such as washin , and/or smoking. Routinely wash work
Physical and chemical				
pearance				
Physical state	Liquid.			
Form	Liquid.			
Color	Clear. Colorless.			
lor	Hydrocarbon-like.			
lor threshold	Not available.			

Evaporation rate	< 1 (Ethyl Ether = 1)		
Flammability (solid, gas)	Not applicable.		
Upper/lower flammability or exp	losive limits		
Flammability limit - lower (%)	0.6 %		
Flammability limit - upper (%)	7 %		
Explosive limit - lower (%)	Not available.		
Explosive limit - upper (%)	Not available.		
Vapor pressure	352.53 mm Hg @ 38°C		
Vapor density	~3 (air = 1)		
Relative density	Not available.		
Solubility(ies)			
Solubility (water)	< 10 % w/w		
Partition coefficient (n-octanol/water)	>1		
Auto-ignition temperature	582.8 °F (306 °C)		
Decomposition temperature	Not available.		
Viscosity	< 3 cSt @ 25°C		
Other information			
Explosive properties	Not explosive.		
Heat of combustion	> 30 kJ/g		
Oxidizing properties	Not oxidizing.		
Percent volatile	100 %		
Specific gravity	0.64 - 0.67 @ 20ºC		
VOC	100 % per US State and Federal Consumer Product Regulations; 669 g/L per SCAQMD Rule 102		
10. Stability and reactivity			
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.		
Chemical stability	Material is stable under normal conditions.		
Possibility of hazardous reactions	Hazardous polymerization does not occur.		
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the		

	flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Isocyanates. Chlorine.
Hazardous decomposition products	Carbon oxides.

# 11. Toxicological information

#### Information on likely routes of exposure

information on fixery routes of ea		
Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.	
Skin contact	Causes skin irritation.	
Eye contact	Causes serious eye irritation.	
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.	
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.	
Information on toxicological effects		
Acute toxicity	May be fatal if swallowed and enters airways.	

Components	Species	Test Results	
Isopropanol (CAS 67-63-0)			
<u>Acute</u>			
Oral			
LD50	Rat	4.7 g/kg	
N-Hexane (CAS 110-54-3)			
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 2000 mg/kg, 4 Hours	
Pentane (CAS 109-66-0)			
Acute			
Oral	<b>D</b> .	0000 //	
LD50	Rat	> 2000 mg/kg	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes serious eye irritatior		
Respiratory or skin sensitizatio	n		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected	to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
ACGIH Carcinogens			
Isopropanol (CAS 67-63- IARC Monographs. Overall	0) Evaluation of Carcinogenicit	A4 Not classifiable as a human carcinogen.	
Not listed. OSHA Specifically Regulate	ed Substances (29 CFR 1910.	001-1050)	
Not regulated. US. National Toxicology Pro	ogram (NTP) Report on Carci	nogens	
Not listed.			
Reproductive toxicity	Suspected of damaging ferti	ity or the unborn child.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	May be fatal if swallowed an	l enters airways.	
Chronic effects	Prolonged inhalation may be	-	
Further information	Symptoms may be delayed.		
12. Ecological information			
Ecotoxicity	The product is not classified	as environmentally hazardous. However, this does not exclude the ent spills can have a harmful or damaging effect on the environment.	
Components	Species	Test Results	
Isopropanol (CAS 67-63-0) Aquatic	-		
Fish	LC50 Bluegill (Lep	mis macrochirus) > 1400 mg/l, 96 hours	
1 1011	LOOD Didegiii (Lepi		

Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 2.101 - 2.981 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

## Persistence and degradability

N-Hexane (CAS 110-54-3)

Partition coefficient n-or	ctanol / water (log Kow)	
LPS® CFC Free	>1	
2-Methylpentane	3.74	
Isopropanol	0.05	
N-Hexane	3.9	
Pentane	3.39	
Mobility in soil	No data available.	
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.	

# 13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company. D001: Waste Flammable material with a flash point <140 F	
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).	
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.	

## 14. Transport information

DOT	
UN number	UN1993
UN proper shipping name	Flammable liquids, n.o.s. (Hexanes and Isopropanol)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	ll
Environmental hazards	
Marine pollutant	No
	r Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB2, T7, TP1, TP8, TP28
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242
ΙΑΤΑ	
UN number	UN1993
UN proper shipping name	Flammable liquid, n.o.s. (Hexanes and Isopropanol)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	
Environmental hazards	No
ERG Code	3H
	<b>r</b> Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
	Allowed with restrictions.
Cargo aircraft only IMDG	Allowed with restrictions.
UN number	UN1993
•••••••	FLAMMABLE LIQUID, N.O.S. (Hexanes and Isopropanol), MARINE POLLUTANT
UN proper shipping name Transport hazard class(es)	PLAMIMABLE LIQUID, N.O.S. (Revalles and isopropation), MARINE POLLUTANT
Class	3
	3
Subsidiary risk	-
Packing group	II

**Environmental hazards** Marine pollutant Yes EmS F-E, S-E Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code DOT FLAMMABLE IQUID IATA; IMDG Marine pollutant **General information** IMDG Regulated Marine Pollutant. 15. Regulatory information **US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4) N-Hexane (CAS 110-54-3) Listed. SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not regulated. Superfund Amendments and Reauthorization Act of 1986 (SARA) Immediate Hazard - Yes **Hazard categories Delayed Hazard - Yes** Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Material name: LPS® CFC Free

SARA 302 Extremely hazard Not listed.	lous substance	
SARA 311/312 Hazardous chemical	Yes	
SARA 313 (TRI reporting) Not regulated.		
Other federal regulations		
Clean Air Act (CAA) Section	112 Hazardous Air Pollutants (HAPs) List	
N-Hexane (CAS 110-54-3	3)	
Clean Air Act (CAA) Section	112(r) Accidental Release Prevention (40 CFR 68.130)	
Pentane (CAS 109-66-0)		
Safe Drinking Water Act (SDWA)	Not regulated.	
FEMA Priority Substance	ces Respiratory Health and Safety in the Flavor Manufacturing	Workplace
Isopropanol (CAS 67	7-63-0) Low priority	
US state regulations	California Safe Drinking Water and Toxic Enforcement Act of 19 is not known to contain any chemicals currently listed as carcing	
US. California. Candida subd. (a))	te Chemicals List. Safer Consumer Products Regulations (Ca	I. Code Regs, tit. 22, 69502.3,
Isopropanol (CAS 67 N-Hexane (CAS 110		
International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### 16. Other information, including date of preparation or last revision

Issue date Version #	03-23-2017 01
Disclaimer	ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.