

SAFETY DATA SHEET

1. Identification

Product identifier	LPS® Micro-X		
Other means of identification			
Part Number	04516		
Recommended use	A fast drying industrial cleaning solvent designed to remove soil and other contaminants.		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/	Distributor information		
Manufacturer			
Manufacturer			
Company name	ITW Pro Brands		
Address	4647 Hugh Howell Rd.		
	Tucker, GA 30084		
Country	(U.S.A.)		
-	Tel: +1 770-243-8800		
In Case of Emergency	1-800-424-9300 (inside U.S.)		
	+001 703-527-3887 (outside U.S.)		
Website	www.lpslabs.com		
E-mail	lpssds@itwprobrands.com		
2. Hazard(s) identification			
Physical hazards	Flammable aerosols	Category 1	
	Gases under pressure	Compressed gas	
Health hazards	Skin corrosion/irritation	Category 2	
	Serious eye damage/eye irritation	Category 2A	
	Reproductive toxicity (fertility)	Category 2	
	Specific target organ toxicity, single exposure	Category 3 narcotic effects	
Environmental hazards	Not classified.		
OSHA defined hazards	Not classified.		
Label elements			
	$ \land \land$		
Signal word	Danger		
Hazard statement	-	nder pressure; may explode if heated. Causes skin	
		cted of damaging fertility or the unborn child. May	
Precautionary statement			
Prevention		handle until all safety precautions have been read	
	spray on an open flame or other ignition sourc	/open flames/hot surfaces No smoking. Do not e. Avoid breathing dust/fume/gas/mist/vapors/spray.	
	gloves/protective clothing/eye protection/face		
Response	IF exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water/soap. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.		

Storage	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-Methylpentane		107-83-5	70 - 80
Isopropanol		67-63-0	5 - 15
Pentane		109-66-0	1 - 10
Carbon Dioxide		124-38-9	1 - 5
N-Hexane		110-54-3	0.1 - 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist. Wash off immediately with soap and plenty of water while removing all contaminated clothes and Skin contact shoes. Get medical attention if irritation develops and persists. Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Eye contact Call a physician or Poison Control Center immediately. Call a physician or poison control center immediately. Only induce vomiting at the instruction of Ingestion medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Irritation of eyes and mucous membranes. Symptoms may include stinging, tearing, redness, Most important swelling, and blurred vision. Defatting of the skin. Vapors have a narcotic effect and may cause symptoms/effects, acute and headache, fatigue, dizziness and nausea. Narcosis. Behavioral changes. Prolonged exposure may delaved cause chronic effects. Provide general supportive measures and treat symptomatically. Keep victim under observation. Indication of immediate Symptoms may be delayed. medical attention and special treatment needed Ensure that medical personnel are aware of the material(s) involved, and take precautions to General information protect themselves. In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Wash contaminated clothing before reuse. 5. Fire-fighting measures

Alcohol resistant foam. Water fog. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, Suitable extinguishing media sand or earth may be used for small fires only. Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire. media Specific hazards arising from By heating and fire, harmful vapors/gases may be formed. Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. the chemical Special protective equipment Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective and precautions for firefighters clothing will only provide limited protection. **Fire fighting** In case of fire and/or explosion do not breathe fumes. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so equipment/instructions without risk. Water runoff can cause environmental damage. Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. In the event of fire and/or explosion do not breathe fumes. Extremely flammable aerosol. General fire hazards

6. Accidental release measures

6. Accidental release meas	sures
Personal precautions, protective equipment and emergency procedures	Consider initial downwind evacuation for at least 500 meters (1/3 mile). Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use foam to blanket spilled material. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills in original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Should be handled in closed systems, if possible. Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Use non-sparking tools and explosion-proof equipment.
	Avoid contact during pregnancy/while nursing. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure.
	Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol.
	Store locked up. Keep away from heat, sparks and open flame. Eliminate sources of ignition.
	Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
Isopropanol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
N-Hexane (CAS 110-54-3)	PEL	1800 mg/m3	
		500 ppm	
Pentane (CAS 109-66-0)	PEL	2950 mg/m3	
		1000 ppm	

US. ACGIH Threshold Limit Values

Components	Туре	Value	
2-Methylpentane (CAS 107-83-5)	STEL	1000 ppm	
	TWA	500 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
Isopropanol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
N-Hexane (CAS 110-54-3)	TWA	50 ppm	
Pentane (CAS 109-66-0)	TWA	1000 ppm	
US. NIOSH: Pocket Guide to Chen	nical Hazards		
Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3	
		500 ppm	
	TWA	980 mg/m3	
		400 ppm	
N-Hexane (CAS 110-54-3)	TWA	180 mg/m3	
		50 ppm	
Pentane (CAS 109-66-0)	Ceiling	1800 mg/m3	
		610 ppm	
	TWA	350 mg/m3	
		120 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Isopropanol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
N-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin d	lesignation	
N-Hexane (CAS 110-54-3	3) Can be absorbed through the skin.	
US ACGIH Threshold Limit \	Values: Skin designation	
N-Hexane (CAS 110-54-3	3) Can be absorbed through the skin.	
Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Provide eyewash station.	
Individual protection measures,	such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye wash fountain is recommended.	
Skin protection		
Hand protection	For prolonged or repeated skin contact use suitable protective gloves. Chemical resistant gloves are recommended.	
Other	Avoid contact with the skin. Wear appropriate chemical resistant clothing.	
Respiratory protection	No personal respiratory protective equipment normally required. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.	
Thermal hazards	None known.	
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	

9. Physical and chemical properties

of the store and one mean of the store of th	
Appearance	Liquid.
Physical state	Gas.
Form	Aerosol.
Color	Clear water-white
Odor	Solvent.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	140.9 °F (60.5 °C) dispensed liquid
Flash point	< 1.4 °F (< -17.0 °C) Tag Closed Cup
Evaporation rate	< 1 (Ethyl Ether = 1)
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	0.6 %
Flammability limit - upper (%)	7 %
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	352.53 mm Hg @ 38°C
Vapor density	~3 (air = 1)
Relative density	Not available.
Solubility(ies)	
Solubility (water)	< 10 % w/w
Partition coefficient (n-octanol/water)	> 1
Auto-ignition temperature	582.8 °F (306 °C)
Decomposition temperature	Not available.
Viscosity	< 3 cSt @ 25°C
Other information	
Heat of combustion	> 30 kJ/g
Percent volatile	100 %
Specific gravity	0.64 - 0.67 @ 20ºC
VOC	96.2 % per U.S, State and Federal Consumer Product Regulations; 669 g/L per SCAQMD Rule 102
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Risk of ignition. Instability caused by elevated temperatures.
Possibility of hazardous	No dangerous reaction known under conditions of normal use.

reactions	
Conditions to avoid	Avoid temperatures exceeding the flash point.
Incompatible materials	Strong oxidizing agents. Isocyanates. Acids. Chlorine.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Skin contact	Causes skin irritation. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed.
Symptoms related to the physical, chemical and	Skin irritation. Defatting of the skin. I include stinging, tearing, redness, sv

Skin irritation. Defatting of the skin. Irritating to eyes and respiratory system. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects


toxicological characteristics

Acute toxicity	Narcotic effects.			
Components	Species		Test Results	
Isopropanol (CAS 67-63-0)				
Acute				
Oral				
LD50	Rat		4.7 g/kg	
N-Hexane (CAS 110-54-3)				
<u>Acute</u>				
Dermal				
LD50	Rabbit> 2000 mg/kg, 4 Hours			
Pentane (CAS 109-66-0)				
Acute				
Oral	Det			
LD50	Rat		> 2000 mg/kg	
Skin corrosion/irritation	Causes skin irritation.			
Serious eye damage/eye irritation	Causes serious eye irritation.			
Respiratory or skin sensitization	n			
Respiratory sensitization	Not a respiratory	Not a respiratory sensitizer.		
Skin sensitization	This product is no	t expected to cause skin sensitiza	ation.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
Carcinogenicity	This product is no	t considered to be a carcinogen b	y IARC, ACGIH, NTP, or OSHA.	
ACGIH Carcinogens				
Isopropanol (CAS 67-63 IARC Monographs. Overall			as a human carcinogen.	
Not listed.	ad Subatanaaa (20	CED 1010 1001 1050		
OSHA Specifically Regulate	ed Substances (29	CFR 1910.1001-1050)		
Not regulated. US. National Toxicology Pr	ogram (NTP) Repo	rt on Carcinogens		
Not listed.	- 3 ()			
Reproductive toxicity	Suspected of damaging fertility or the unborn child.			
Specific target organ toxicity - single exposure	Narcotic effects.			
Specific target organ toxicity - repeated exposure	Not classified.			
Aspiration hazard	Not likely, due to	Not likely, due to the form of the product.		
Chronic effects	None known.			
Further information	None known.			
12. Ecological informatio				
Ecotoxicity		fe with long lasting effects.		
Components		Decies	Test Results	
Isopropanol (CAS 67-63-0)				
Aquatic				
Fish	LC50 BI	uegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours	
		· · ·	-	

Material name: LPS® Micro-X

Components		Species	Test Results
N-Hexane (CAS 110-54-3)			
Aquatic			
Fish	LC50	Fathead minnow (Pime	phales promelas) 2.101 - 2.981 mg/l, 96 hours
Persistence and degradability	Not inher	ently biodegradable.	
Bioaccumulative potential	No data available for this product.		
Partition coefficient n-octa	nol / water ((log Kow)	
LPS® Micro-X		> 1	
2-Methylpentane		3.74	
Isopropanol		0.05	
N-Hexane		3.9	
Pentane		3.39	
Mobility in soil	Readily a	bsorbed into soil.	
Other adverse effects	None kno	own.	
13. Disposal consideratio	ns		
Disposal instructions	and its co sewers/w container	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazardous waste code		aste Flammable material with aste Reactive material	a flash point <140 F
Waste from residues / unused products	product r	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).	
Contaminated packaging			an approved waste handling site for recycling or disposal. product residue, follow label warnings even after container is
14. Transport information	l		
DOT			
UN number	UN1950		
		flammable	

	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not available.
	Environmental hazards	
	Marine pollutant	No
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
	Packaging exceptions	306
	Packaging non bulk	None
	Packaging bulk	None
IAT	Α	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Packing group	Not available.
	Environmental hazards	No.
	ERG Code	2X
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
	Other information	
	Passenger and cargo aircraft	Allowed with restrictions.



DOT





General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

N-Hexane (CAS 110-54-3)

Listed.

SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not regulated. Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No SARA 302 Extremely hazardous substance Not listed. SARA 311/312 Hazardous Yes chemical SARA 313 (TRI reporting) Not regulated. Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List N-Hexane (CAS 110-54-3) Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Pentane (CAS 109-66-0) Safe Drinking Water Act Not regulated. (SDWA) FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace Isopropanol (CAS 67-63-0) Low priority **US state regulations** US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a)) Isopropanol (CAS 67-63-0) N-Hexane (CAS 110-54-3) International Inventories Country(s) or region On inventory (yes/no)* Inventory name Australian Inventory of Chemical Substances (AICS) Australia Yes Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No China Inventory of Existing Chemical Substances in China (IECSC) Yes European Inventory of Existing Commercial Chemical Europe Yes Substances (EINECS)

Philippines Philippine Inventory of Chemicals and Chemical Substances (PICCS) United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory *A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s)

Existing Chemicals List (ECL)

New Zealand Inventory

A "No" indicates that one or more components of the product comply with the inventory requirements administered by the governing country(s).

European List of Notified Chemical Substances (ELINCS)

Inventory of Existing and New Chemical Substances (ENCS)

16. Other information, including date of preparation or last revision

Issue date	09-15-2015
Revision date	03-23-2017
Version #	03

Europe

Japan Korea

New Zealand

No

Yes

Yes

Yes

Yes

Yes

Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Hazard(s) identification: Hazard statement Hazard(s) identification: Prevention Hazard(s) identification: Response Composition / Information on Ingredients: Disclosure Overrides Handling and storage: Precautions for safe handling Toxicological information: Chronic effects Toxicological information: Specific target organ toxicity - repeated exposure Regulatory Information: Risk Phrases - Labeling GHS: Classification