



SAFETY DATA SHEET

1. Identification

Product identifier LPS® Cold Galvanize
Other means of identification
Part Number 05128, C05128
Recommended use A zinc rich industrial maintenance primer designed for rust and corrosion protection.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Pro Brands
Address 4647 Hugh Howell Rd.
Tucker, GA 30084
Country (U.S.A.)
Tel: +1 770-243-8800
In Case of Emergency 1-800-424-9300
1-703-527-3887
Website www.lpslabs.com
E-mail lpssds@itwprobrands.com

Supplier

ITW Permatex Canada
1-35 Brownridge Road
Halton Hills, ON, L7G 0C6
Canada

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, dermal	Category 4
	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1B
	Carcinogenicity	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity, repeated exposure	Category 1 (Central Nervous System)
Specific target organ toxicity, repeated exposure	Category 2 (auditory organ, Lung, Kidney)	
Environmental hazards	Not classified.	

Label elements



Signal word

Danger

Hazard statement

Highly flammable liquid and vapor. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs (Central Nervous System) through prolonged or repeated exposure. May cause damage to organs (auditory organ, Lung, Kidney) through prolonged or repeated exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.

Storage

Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

None known.

Supplemental information

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Metallic Zinc		7440-66-6	60 - 70
ACETONE		67-64-1	5 - 10
Xylene		1330-20-7	1 - 10
ETHYLBENZENE		100-41-4	1 - 3
STODDARD SOLVENT		8052-41-3	1 - 3
ZINC OXIDE		1314-13-2	1 - 3
TOLUENE		108-88-3	0.1 - 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

Narcosis. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Discomfort in the chest. Shortness of breath. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Edema. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Dry sand. Carbon dioxide (CO2).

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water surface. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ACETONE (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm	
STODDARD SOLVENT (CAS 8052-41-3)	TWA	100 ppm	
TOLUENE (CAS 108-88-3)	TWA	20 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ZINC OXIDE (CAS 1314-13-2)	TWA	100 ppm	
	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
ACETONE (CAS 67-64-1)	STEL	1800 mg/m3	
		750 ppm	
	TWA	1200 mg/m3	
ETHYLBENZENE (CAS 100-41-4)	STEL	500 ppm	
		543 mg/m3	
	TWA	125 ppm	
STODDARD SOLVENT (CAS 8052-41-3)	TWA	434 mg/m3	
		100 ppm	
TOLUENE (CAS 108-88-3)	TWA	572 mg/m3	
		100 ppm	
Xylene (CAS 1330-20-7)	TWA	188 mg/m3	
		50 ppm	
ZINC OXIDE (CAS 1314-13-2)	STEL	651 mg/m3	
		150 ppm	
	TWA	434 mg/m3	
	STEL	100 ppm	Respirable.
	TWA	2 mg/m3	Respirable.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
ACETONE (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm	
STODDARD SOLVENT (CAS 8052-41-3)	STEL	580 mg/m3	
	TWA	290 mg/m3	
TOLUENE (CAS 108-88-3)	TWA	20 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	
ZINC OXIDE (CAS 1314-13-2)	STEL	10 mg/m3	Respirable.
	TWA	2 mg/m3	Respirable.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
ACETONE (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm	
STODDARD SOLVENT (CAS 8052-41-3)	TWA	100 ppm	
TOLUENE (CAS 108-88-3)	TWA	20 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
ZINC OXIDE (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
ACETONE (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm	
STODDARD SOLVENT (CAS 8052-41-3)	TWA	100 ppm	
TOLUENE (CAS 108-88-3)	TWA	20 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	
ZINC OXIDE (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value	Form
ACETONE (CAS 67-64-1)	STEL	2380 mg/m3	
		1000 ppm	
	TWA	1190 mg/m3	
ETHYLBENZENE (CAS 100-41-4)	STEL	500 ppm	
		543 mg/m3	
	TWA	125 ppm	
STODDARD SOLVENT (CAS 8052-41-3)		434 mg/m3	
		100 ppm	
	TWA	525 mg/m3	
TOLUENE (CAS 108-88-3)		100 ppm	
		188 mg/m3	
	TWA	50 ppm	
Xylene (CAS 1330-20-7)	STEL	651 mg/m3	
		150 ppm	
	TWA	434 mg/m3	
ZINC OXIDE (CAS 1314-13-2)	STEL	100 ppm	
		10 mg/m3	Fume.
	TWA	5 mg/m3	Fume.
		10 mg/m3	Total dust.

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
ACETONE (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
TOLUENE (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

Canada - Alberta OELs: Skin designation

TOLUENE (CAS 108-88-3)

Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

TOLUENE (CAS 108-88-3)

Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

TOLUENE (CAS 108-88-3)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Liquid.

Color

Grey.

Odor

Aromatic. Hydrocarbon-like.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling range

Not available.

Flash point

< 73.4 °F (< 23.0 °C)

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

> 1 kPa @ 25°C

Vapor density

> 1 (air = 1)

Relative density

Not available.

Solubility(ies)

Solubility (water)

Insoluble in water

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

Not available.

Decomposition temperature

Not available.

Viscosity

3000 - 4500 cSt

Other information

Density	18.97 g/cm ³
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Percent volatile	25.7 %
Specific gravity	2.27 @ 25°C
VOC	335.5 g/l per U.S. State and Federal Architectural Coating Regulations.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens.
Hazardous decomposition products	Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition.

11. Toxicological information**Information on likely routes of exposure**

Inhalation	Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Narcosis. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Discomfort in the chest. Shortness of breath. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Edema.

Information on toxicological effects

Acute toxicity Harmful if inhaled. Harmful in contact with skin.

Components	Species	Test Results
ACETONE (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rabbit	> 20 ml/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	50.1 mg/l, 4 Hours
Oral		
LD50	Rat	9.1 ml/kg
ETHYLBENZENE (CAS 100-41-4)		
Acute		
Dermal		
LD50	Rabbit	17.8 ml/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	4000 ppm, 4 Hours
Oral		
LD50	Rat	3500 mg/kg

Components	Species	Test Results
Metallic Zinc (CAS 7440-66-6)		
Acute		
Inhalation		
<i>Dust</i>		
LC50	Rat	> 5410 mg/m3, 4 Hours
Oral		
LD50	Rat	630 mg/kg
Naphtha, Petroleum, Hydrotreated Heavy (CAS 64742-48-9)		
Acute		
Dermal		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 4980 mg/m3, 4 Hours
Oral		
LD50	Rat	4820 mg/kg
TOLUENE (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	14.1 ml/kg
Inhalation		
LC50	Rat	8000 ppm, 4 Hours
Oral		
LD50	Rat	2.6 g/kg
Xylene (CAS 1330-20-7)		
Acute		
Dermal		
LD50	Rabbit	> 5000 ml/kg, 4 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	6700 ppm, 4 Hours
Oral		
LD50	Rat	10 ml/kg
ZINC OXIDE (CAS 1314-13-2)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 5700 mg/m3, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	

ACGIH Carcinogens

ACETONE (CAS 67-64-1)

ETHYLBENZENE (CAS 100-41-4)

TOLUENE (CAS 108-88-3)

Xylene (CAS 1330-20-7)

A4 Not classifiable as a human carcinogen.

A3 Confirmed animal carcinogen with unknown relevance to humans.

A4 Not classifiable as a human carcinogen.

A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

ACETONE (CAS 67-64-1)

ETHYLBENZENE (CAS 100-41-4)

TOLUENE (CAS 108-88-3)

Xylene (CAS 1330-20-7)

Not classifiable as a human carcinogen.

Confirmed animal carcinogen with unknown relevance to humans.

Not classifiable as a human carcinogen.

Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

ETHYLBENZENE (CAS 100-41-4)

TOLUENE (CAS 108-88-3)

Xylene (CAS 1330-20-7)

2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Specific target organ toxicity - single exposure

Not classified.

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure. May cause damage to organs (auditory organ, Lung, Kidney) through prolonged or repeated exposure.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Causes damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Further information

Symptoms may be delayed.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
ACETONE (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
ETHYLBENZENE (CAS 100-41-4)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours
Metallic Zinc (CAS 7440-66-6)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	2.8 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.56 mg/l, 96 hours
TOLUENE (CAS 108-88-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
Xylene (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours
ZINC OXIDE (CAS 1314-13-2)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	2246 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

ACETONE	-0.24
ETHYLBENZENE	3.15
STODDARD SOLVENT	3.16 - 7.15
TOLUENE	2.73
Xylene	3.12 - 3.2

Mobility in soil No data available.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

UN number	UN1263
UN proper shipping name	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base (Metallic Zinc), MARINE POLLUTANT
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number	UN1263
UN proper shipping name	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	

Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1263
UN proper shipping name	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base (Metallic Zinc), MARINE POLLUTANT
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	Yes

EmS

F-E, S-E

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.


Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

IATA; IMDG; TDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

ACETONE (CAS 67-64-1)

ETHYLBENZENE (CAS 100-41-4)

TOLUENE (CAS 108-88-3)

Xylene (CAS 1330-20-7)

Precursor Control Regulations

ACETONE (CAS 67-64-1)

Class B

TOLUENE (CAS 108-88-3)

Class B

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

16. Other information

Issue date 09-08-2016

Version # 01

Disclaimer ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Product Uses
Composition / Information on Ingredients: Ingredients
Physical & Chemical Properties: Multiple Properties
Transport Information: Proper Shipping Name/Packing Group
Regulatory Information: United States
HazReg Data: North America
GHS: Qualifiers