

SAFETY DATA SHEET

1. Identification

Product identifier PS90 G-49™ Other means of identification 06420, C06420 Part Number 06420, C06420 Recommended use A solvent designed to remove grease, grime, oil and other oil-based contaminants. Recommended restrictions None known. Manufacturer/Importer/Suppiter/Suptiter/Supriter/Supriter/Suppiter/	1. Identification				
Part Number06420, C06420Recommended useA solvent designed to remove grease, grime, oil and other oil-based contaminants.Recommended testrictionsNone known.Manufacturer/Importer/Supitar/Sup	Product identifier	LPS® G-49™			
Recommended restrictions Asolvent designed to remove grease, grimi and other oil-based contaminants. Recommended restrictions None known. Manufacturer/Importer/Sup-Uis-Uistubar information Superior Gompany name ITW Pro Brands Superior Address 4647 Hugh Howell Rd. Superior Address 100 Pro 243-8800 Superior Tors. 27-3887 Superior Superior None Section 1980-424-9300 Superior 100 Costny 1980-824-9300 Superior Superior E-mail 1980-824-9300 Superior Superior Superior Fundation Hills Cond Scom Superior Superior Superior Superior Superior Superior Supplier None-241-830 Superior Category 1 Superior Superior <th< th=""><th>Other means of identification</th><th></th><th></th></th<>	Other means of identification				
Recommended restrictions None known. Manufacturer/Importer/Supplier/Justributor information Manufacturer Company name ITW Pro Brands Address 6437 Hugh Howell Rd. Tucker, GA 30084 Tucker, GA 30084 Country (U.S.A) Tel: +1 770-243-8800 Tel: +1 770-243-8800 In Case of Emergency 1-800-424-3000 1-703-527-3887 Website Www.lpslabs.com Email E-mail Ipssds@itwprobrands.com Supplier ITW Permatex Canada 1-350-241-8334 Tel: +1.770-243-8800 Jass Grownridge Road Haiton Hills, ON, L7G 0C6 Canada 1-300-241-8334 Jass Grownridge Road Haiton Hills, ON, L7G 0C6 Canada 1-300-241-8334 Jass Inder pressure Category 1 Gases under pressure Category 2 Benitic target organ toxicity, single exposure Category 3 narcotic effects Environmental hazards Not classified. Label elements Signal word Basgif word Darger Signal word Darger Hazard st	Part Number	06420, C06420			
Manufacturer/Importer/Supplier/Distributor information Manufacturer Company name IW Pro Brands Address 4647 Hugh Howell Rd. Tucker, GA 30084 Country (U.S.A.) Tei: +1770-243-8800 In Case of Emergency 1-800-424-9300 1-703-527-3887 Website www.lpslabs.com E-mail lpsds@ltwprobrands.com Supplier lpsds@ltwprobrands.com Supplier UW Permatex Canada 1-35 Brownridge Road Haton Hills, ON, L7G 0C6 Canada 1-35 Brownridge Road Haton Hills, ON, DY Canada 1-35 Brownridge Road Haton Hills, ON, MY Canada 1-35 Brownridge Road Haton Hills, ON, MY Canada 1-35 Brownridge Road Haton May canada	Recommended use	A solvent designed to remove grease, grime, oil and other oil-based contaminants.			
ManufacturerITW Pro BrandsCompany nameITW Pro Brands4647 Hugh Howell Rd. Tucker, GA 30084Country(U.S.A.) Tei: +1 770-243-8800In Case of Emergency1-800-424-9300 1-703-527-3887Websitewww.lpslabs.comE-mailIpssds@livprobrands.comSupplierIpssds@livprobrands.comSupplierTTW Permatex Canada 1-800-241-8334J. Hazard(s) identificationITW 2-43-834Physical hazardsFlammable aerosolsCategory 1 Compressed gasGases under pressureCategory 2 Serius schinztion, skinCategory 1 Category 1 Category 1 Sepcific target organ toxicity, single exposureLabel elementsVersitie Canada Category 1 Serius schinztion, skinCategory 3 narcotic effectsEnvironmental hazardsDangerVersitie Canada Category 3 narcotic effectsEnvironmental hazardsDangerExtremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin drivistion. May cause an allergic skin reactos. Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin drivistion. May cause an allergic skin reactos.	Recommended restrictions	None known.			
Company nameITW Pro BrandsAddress4647 Hugh Howell Rd. Tucker, GA 30084Country(U.S.A) Tel: +1 770-243-8800In Case of Emergency1-800-424-9300 1-703-527-3887Websitewww.lpslabs.comE-maillpssds@itwprobrands.comSupplierITW Permatex Canada Haton Hills, ON, L7G 0CG Canada 1-800-241-83342. Hazard(s) identificationITW Permatex Canada Haton Hills, ON, L7G 0CG Canada 1-800-241-8334Physical hazardsFlammable aerosolsGases under pressureCategory 1 Category 2Bertization, skinCategory 1 Category 1 Serositified in Serie VNot classified.Category 1 Category 1 Category 1Environmental hazardsNot classified. VBagel wordOangerHazard statementFlammable aerosol. Contains gas under pressure; may explode if heated. Causes skin iritation. May cause an allergic skin reaction. Series serieus eye iritation. May cause drowsiness or dizziness.	Manufacturer/Importer/Supplier/	Distributor information			
Address 4647 Hugh Howell Rd. Tucker, GA 30084 Country (U.S.A.) Tel: +1 770-243-8800 In Case of Emergency 1-800-424-9300 1-703-527-3887 Website Www.lpslabs.com	Manufacturer				
Lucker, GA 30084CountryTucker, GA 30084(U.S.A.)Tucker, Tyr0-243-8800Tel: +1 770-243-8800Tyr0-243-8800In Case of Emergency1-800-424-93001-703-527-3887WebsiteWebsiteWww.lpslabs.comE-mailUpsds@ltwprobrands.comSupplierTirW Permatex Canada 1-800-241-83342. Hazard(s) identificationCategory 1Physical hazardsFlammable aerosolsCategory 2Gases under pressureCategory 2Bealth hazardsSkin corrosion/irritationCategory 2Bealth hazardsNot classified.Environmental hazardsNot classified.Environmental hazardsOat geagCategory 1Signal wordDangerHazard statementExtremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin crosing ciritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause and crosing ciritation. Causes serious eye irritation. May cause and crosing ciritation. Causes serious eye irritation. May cause	Company name	ITW Pro Brands			
Country(U.S.A.) Tei: +1 770-243-8800 1-800-424-9300 1-800-424-9300 1-800-424-9300 1-800-424-9300 1-800-424-9300 1-800-424-9300 1-800-424-9300Websitewww.lpsiabs.com 1-80-824-8800 1-805-800-800-800-800-800-800-800-800-800	Address	4647 Hugh Howell Rd.			
Tel: +1 770-243-8800In Case of Emergency1-800-424-9300 1-703-527-3887Websitewww.lpslabs.comE-mailIpseds@ltwprobrands.comSupplierITW Permatex Canada 1-35 Envonridge Road Halton Hills, ON, L7G 0C6 Canada 1-800-241-83342. Hazard(s) identificationEPhysical hazardsFlammable aerosolsCategory 1 Compressed gasHealth hazardsFlammable aerosolsCategory 2 Canada 1-800-241-8334Physical hazardsFlammable aerosolsCategory 2 Category 2Benditi hazardsFlammable aerosolsCategory 1 Category 2Environmental hazardsNot classified.Environmental hazardsEverel of gan toxicity, single exposure Signal wordCategory 3 narcotic effectsSignal wordDangerHazard statementExtremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin reaction, skin corroson strintation. May cause an allergic skin reaction. Lorostains gas under pressure; may explode if heated. Causes skin reaction, skin corrostains gas under pressure; may explode if heated. Causes skin reaction skin reaction. Lorostains gas under pressure; may explode if heated. Causes skin reaction skin reaction. Lorostains gas under pressure; may explode if heated. Causes skin reaction. Skin reaction. Lorostains gas under pressure; may explode if heated. Causes skin reaction. Skin reaction. Lorostains gas under pressure; may explode if heated. Causes skin reaction. Lorostains gas under pressure; may explode if heated. Causes skin reaction. Lorostains gas under pressure; may explode if heated. Causes skin reaction. Lorostains gas under pressure; may explode if heated. Causes skin t					
In Case of Emergency1-800-424-9300 1-703-527-3887Websitewww.lsplabs.comE-maillpssds@itwprobrands.comSupplierImprovements Canada 1-35 Brownridge Road Halton Hills, ON, L7G 0C6 Canada 1-800-241-83342. Hazard(s) identificationCategory 1 Gases under pressurePhysical hazardsFlammable aerosolsCategory 2 Category 2A Category 2AHealth hazardsSkin corrosion/irritation Sensitization, skinCategory 1 Category 3 narcotic effectsEnvironmental hazardsNot classified.Environmental hazardsDangerSignal wordDangerHazard statementExtremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin reaction. Skin causes serious eye irritation. May causes an allergic skin reaction. Causes serious eye irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause	Country				
i-703-527-3887Websitei-703-527-3887Websiteipsexds@itwprobrands.comE-mailIpsexds@itwprobrands.comSupplierITW Permatex Canada Haiton Hills, ON, L7G OC6 Canada 1-800-241-83342. Hazard(s) identificationEategory 1 Gases under pressurePhysical hazardsFlammable aerosolsCategory 1 Cangory 2Health hazardsSkin corrosion/irritationCategory 2 Category 1 Seroius eye damage/eye irritationEnvironmental hazardsSkin corrosion/irritationCategory 2 Category 1 Category 1 Seroius eye damage/eye irritationEnvironmental hazardsNot classified.Eategory 3 narcotic effectsEnvironmental hazardsDangerExtremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin riritation. May cause an allergic skin reaction. Kay cause an allergic skin reaction. Kay cause an allergic skin reaction. Kay cause serious eye irritation. May cause an allergic skin reaction.					
Websitewww.lpslabs.comE-mailwww.lpslabs.comSupplierITW Permatex Canada 1-35 Brownridge Road Halton Hills, ON, L7G 0C6 Canada 1-800-241-8334D. Hazard(s) identificationEPhysical hazardsFlammable aerosolsCategory 1Gases under pressureCompressed gasHealth hazardsSkin corrosion/irritationCategory 2AGenous eve damage/eye irritationCategory 1Sensitization, skinCategory 1Environmental hazardsNot classified.Environmental hazardsVot classified.Signal wordDangerHazard statementStremely flammable aerosol. Contains gas: under pressure; may explode if heated. Causes skin reaction. May cause an allergic skin reaction. Skin security single explose.	In Case of Emergency				
E-maillpsds@itwprobrands.comSupplierITW Permatex Canada 1-35 Brownridge Road Halton Hills, ON, L7G 0C6 Canada 1-800-241-83342. Hazard(s) identificationIPhysical hazardsFlammable aerosolsGases under pressureCompressed gasHealth hazardsSkin corrosion/irritationGases under pressureCompressed gasForous eye damage/eye irritationCategory 2ASerious eye damage/eye irritationCategory 1Sopeific target organ toxicity, single exposusCategory 1Sopeific target organ toxicity, single exposusCategory 3 narcotic effectsLabel elementsImage Surger Surg					
SupplierITW Permatex Canada 1-35 Brownridge Road Halton Hills, ON, L7G 0C6 Canada 1-800-241-8334Z. Hazard(s) identificationFlammable aerosolsCategory 1Physical hazardsFlammable aerosolsCategory 2Bealth hazardsSkin corrosion/irritationCategory 2Kealth hazardsSkin corrosion/irritationCategory 2Bealth hazardsSkin corrosion/irritationCategory 2Bealth hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2Serious eye damage/eye irritationCategory 1Specific target organ toxicity, single exposureCategory 3 narcotic effectsEnvironmental hazardsNot classified.Environmental hazardsDangerSignal word Hazard statementDangerHazard statementExtremely flammable aerosol. Contains gas urb pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reactio Causes serious eye irritation. May cause drowsiness or dizziness.		•			
1-35 Brownridge Road Halton Hills, ON, L7G OC6 Canada 1-800-241-83342. Hazard(s) identificationPhysical hazardsFlammable aerosols Gases under pressure Gases under pressure Compressed gasHealth hazardsSkin corrosion/irritation Serious eye damage/eye irritation Sensitization, skin Specific target organ toxicity, single exposure Category 1 Specific target organ toxicity, single exposure Category 3 narcotic effectsEnvironmental hazardsDangerSignal word Hazard statementDangerKategory I Signal word Hazard statementDanger					
Physical hazardsFlammable aerosolsCategory 1Gases under pressureCompressed gasHealth hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2ASensitization, skinCategory 1Specific target organ toxicity, single exposureCategory 3 narcotic effectsEnvironmental hazardsNot classified.Label elementsImage: Compressure to the second s	Supplier	1-35 Brownridge Road Halton Hills, ON, L7G 0C6 Canada			
Health hazardsGases under pressureCompressed gasHealth hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2ASensitization, skinCategory 1Specific target organ toxicity, single exposureCategory 3 narcotic effectsEnvironmental hazardsNot classified.Label elementsImage: Signal wordDangerHazard statementExtremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.	2. Hazard(s) identification				
Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2ASensitization, skinCategory 1Specific target organ toxicity, single exposureCategory 3 narcotic effectsEnvironmental hazardsNot classified.Label elementsImage: Category 3 narcotic effectsSignal wordDangerHazard statementExtremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.	Physical hazards	Flammable aerosols	Category 1		
Serious eye damage/eye irritationCategory 2ASensitization, skinCategory 1Specific target organ toxicity, single exposureCategory 3 narcotic effectsEnvironmental hazardsNot classified.Label elementsImage: Comparison of the section of		Gases under pressure	Compressed gas		
Sensitization, skinCategory 1Specific target organ toxicity, single exposureCategory 3 narcotic effectsEnvironmental hazardsNot classified.Label elementsImage: Comparison of the sense o	Health hazards	Skin corrosion/irritation	Category 2		
Environmental hazardsSpecific target organ toxicity, single exposure Category 3 narcotic effects Not classified.Label elementsImage: Category 3 narcotic effects DangerSignal word Hazard statementDanger Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin riritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.		Serious eye damage/eye irritation	Category 2A		
Environmental hazards Not classified. Label elements Image: Comparison of the second of t		Sensitization, skin	Category 1		
Label elements Image: Constant of the second of the se		Specific target organ toxicity, single exposure	Category 3 narcotic effects		
Signal word Danger Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.	Environmental hazards	Not classified.			
Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.	Label elements				
Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.					
irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.	Signal word	Danger			
Precautionary statement	Hazard statement	irritation. May cause an allergic skin reaction.	nder pressure; may explode if heated. Causes skin Causes serious eye irritation. May cause		
	Precautionary statement				

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves.

Response IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Prevention

Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards	None known.
Supplemental information	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	70 - 80
Carbon Dioxide		124-38-9	1 - 10
Distillates Petroleum Hydrotreated Light		64742-47-8	1 - 10
d-limonene		5989-27-5	1 - 10

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
Environmental precautions	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

ACGIH	_		F
Components	Туре	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	TWA	5 mg/m3	Oil mist
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
Canada. Alberta OELs (Occupati	onal Health & Safety Code, Sc	hedule 1, Table 2)	
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	1800 mg/m3	
		750 ppm	
	TWA	1200 mg/m3	
		500 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
/		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	

Components		Туре		v	alue	Form
Acetone (CAS 67-64-1)		STEL		5	00 ppm	
		TWA		2	50 ppm	
Carbon Dioxide (CAS 124-38-9)		STEL		1	5000 ppm	
		TWA			000 ppm	
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)		TWA		2	00 mg/m3	Non-aerosol.
Canada. Manitoba OELs Components	(Reg. 217/2006	, The Wo Type	rkplace Safety A		alue	
Acetone (CAS 67-64-1)		STEL		5	00 ppm	
		TWA		2	50 ppm	
Carbon Dioxide (CAS 124-38-9)		STEL			0000 ppm	
		TWA		5	000 ppm	
Canada. Ontario OELs. (Control of Expe		Biological or Che			
Components		Туре		V	alue	
Acetone (CAS 67-64-1)		STEL			50 ppm	
		TWA			00 ppm	
Carbon Dioxide (CAS 124-38-9)		STEL			0000 ppm	
		TWA			000 ppm	
Canada. Quebec OELs. (Components	Ministry of Lab	or - Regu Type	Ilation Respectir		of the Work En /alue	vironment)
Acetone (CAS 67-64-1)		STEL		2	380 mg/m3	
					000 ppm	
		TWA			190 mg/m3	
Orale and Dissider (OAO		OTEL			00 ppm	
Carbon Dioxide (CAS 124-38-9)		STEL		5	4000 mg/m3	
)				3	0000 ppm	
		TWA		9	000 mg/m3	
				5	000 ppm	
ogical limit values						
ACGIH Biological Expos Components	ure Indices Value		Determinant	Specimen	Sampling 1	Time
Acetone (CAS 67-64-1)	25 mg/l		Acetone	Urine	*	
* - For sampling details, pl	ease see the sc	ource doci	ument.			
osure guidelines						
Canada - British Columb	ia OELs: Skin (designati	on			
Distillates Petroleum I 64742-47-8)		-		e absorbed thro	ough the skin.	
propriate engineering	Good gene	eral ventil	ation (typically 10	air changes per	r hour) should b	e used. Ventilation rates
trols	should be or other er exposure l	matched ngineering imits have	to conditions. If a controls to maint	oplicable, use p ain airborne lev shed, maintain	rocess enclosu els below recor airborne levels	res, local exhaust ventilat nmended exposure limits to an acceptable level. Ey
vidual protection measur Eye/face protection	es, such as pe	rsonal pr		ent		
Skin protection						
		onriato ch	nemical resistant	aloves		
Hand protection	wear appr	opnate ci	ionnour roolotunt ;	gio (00.		
Hand protection Other		•	nemical resistant	-		
-	Wear appr	opriate cl ble levels	nemical resistant of are exceeded us	clothing.	anical filter / org	anic vapor cartridge or ar

Material name: LPS® G-49™

Thermal hazards

General hygiene considerations Wear appropriate thermal protective clothing, when necessary.

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Clear water-white.
Odor	Acetone. Orange.
Odor threshold	Not available.
рН	Not available
Melting point/freezing point	Not established
Initial boiling point and boiling range	Not established
Flash point	-4.0 °F (-20.0 °C) Tag Closed Cup (estimated)
Evaporation rate	0.2 BuAc
Flammability (solid, gas)	Flammable gas.
Upper/lower flammability or expl	losive limits
Flammability limit - lower (%)	2.5 %
Flammability limit - upper (%)	12.8 %
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not established
Vapor density	Not established
Relative density	Not available.
Solubility(ies)	
Solubility (water)	80 % w/w
Partition coefficient (n-octanol/water)	Not established
Auto-ignition temperature	Not established
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	6.70 lb/gal @ 25°C
Explosive properties	Not explosive.
Heat of combustion	25 - 30 kJ/g
Oxidizing properties	Not oxidizing.
Percent volatile	100 %
Specific gravity	0.81 @ 20°C
VOC	9.45 % per US State and Federal Consumer Product Regulations
10. Stability and reactivity	
	The product is stable and per prosting upday permit conditions of

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Aluminum.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity	Narcotic effects.		
Components	Species	Test Results	
Acetone (CAS 67-64-1)			
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 20 ml/kg, 24 Hours	
Inhalation			
Vapor			
LC50	Rat	50.1 mg/l, 4 Hours	
Oral			
LD50	Rat	9.1 ml/kg	
Distillates Petroleum Hydrotreat	ed Light (CAS 64742-47-8)		
<u>Acute</u>			
Dermal LD50	Rabbit	· 2000 mg/kg	
	Raddil	> 2000 mg/kg	
Inhalation			
<i>Vapor</i> LC50	Rat	> 4.5 mg/l, 4 Hours	
Oral	nat	> 4.5 mg/l, 4 hours	
LD50	Rat	> 5000 mg/kg	
d-limonene (CAS 5989-27-5)			
Acute			
Oral			
LD50	Rat	> 2000 mg/kg	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye Causes serious eye irritation. irritation		n.	
Respiratory or skin sensitizati	on		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	May cause sensitization by	skin contact.	
Germ cell mutagenicity	No data available to indicat mutagenic or genotoxic.	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
ACGIH Carcinogens			
Acetone (CAS 67-64-1) Canada - Manitoba OELs:		A4 Not classifiable as a human carcinogen.	
Acetone (CAS 67-64-1)		Not classifiable as a human carcinogen.	
IARC Monographs. Overal d-limonene (CAS 5989	Il Evaluation of Carcinogenici	ty 3 Not classifiable as to carcinogenicity to humans.	

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not likely, due to the form of the product.	
Chronic effects	Prolonged inhalation may be harmful.	
Further information	Symptoms may be delayed.	
12. Ecological information		

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	1 5	Species	Test Results		
Acetone (CAS 67-64-1)					
Aquatic					
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours		
Distillates Petroleum Hydrotr	eated Light (CAS	5 64742-47-8)			
Aquatic					
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours		
d-limonene (CAS 5989-27-5))				
Aquatic					
Crustacea	EC50	Water flea (Daphnia pulex)	69.6 mg/l, 48 hours		
Fish	LC50	Fathead minnow (Pimephales promelas)	0.619 - 0.796 mg/l, 96 hours		
ersistence and degradability	No data is ava	ailable on the degradability of this product.			
ioaccumulative potential					
Partition coefficient n-octa	nol / water (log	Kow)			
Acetone		-0.24			
d-limonene		4.232			
lobility in soil		No data available.			
ther adverse effects	None known.	None known.			
3. Disposal consideratio	ons				
isposal instructions	under pressu	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.			
ocal disposal regulations	Dispose in ac	cordance with all applicable regulations.			
azardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.				
		Flammable material with a flash point <14 Reactive material	0 F		
/aste from residues / unused roducts	product residu	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).			
ontaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.				
4. Transport information	ı				
DG					
UN number	UN1950	UN1950			
UN proper shipping name	AEROSOLS,	flammable, MARINE POLLUTANT			

Transport hazard class(es) Class 2.1

Material name: LPS® G-49™

Subsidiary risk-Packing groupNot applicable.Environmental hazardsYesSpecial precautions for userRead safety instructions, SDS and emergency procedures before handling.

ΙΑΤΑ

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS, flammable (d-limonene), MARINE POLLUTANT
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	Not available.
• •	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not applicable.
Annex II of MARPOL 73/78 and	
the IBC Code	

IATA; IMDG; TDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant. Ensure compliance with applicable regulations.

15. Regulatory information

Canadian regulations		
Controlled Drugs and Subst	ances Act	
Not regulated.		
Export Control List (CEPA 1	999, Schedule 3)	
Not listed.		
Greenhouse Gases	1.28.0)	
Carbon Dioxide (CAS 124 Ontario. Toxic Substances.	Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)	
Acetone (CAS 67-64-1)		
Precursor Control Regulation	ons	
Acetone (CAS 67-64-1)	Class B	
International regulations		
Stockholm Convention		
Not applicable. Rotterdam Convention		
Not applicable.		
Kyoto protocol		
Carbon Dioxide (CAS 124	1-38-9) Listed.	
Montreal Protocol		
Not applicable. Basel Convention		
Not applicable.		
International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date	01-29-2017
Version #	01
Disclaimer	ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Product and Company Identification: Product Uses Composition / Information on Ingredients: Ingredients Physical & Chemical Properties: Multiple Properties Regulatory Information: Risk Phrases - Labeling HazReg Data: North America GHS: Classification