



F-104° Solvent Degreaser



FEATURES

- Heavy-duty degreaser
- 104°F (40°C) flash point
- Controlled evaporation
- Safe to use on most surfaces
- Nonconductive
- No rinsing and no residue
- Inverta Spray Valve allows one to spray in an upright or inverted position

MANUFACTURING APPLICATIONS

- Aircraft Structures
- Chains
- Gears
- Cables
- Cranes
- Cowlings
- Forklifts
- Air Compressor
- Bonding Prep
- Power Tools
- Landing Gear
- Terminals

SPECIFICATIONS AND APPROVALS

- Learjet LES 1239J

IS (IDENTIFICATION SYSTEM)



AVAILABLE PRODUCTS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
04920	C04920	15 wt. oz./425 g/532 mL	Aerosol	12	15 lbs.
04905	C04905	5 gal. (18.93 L)	Pail	1	42 lbs.
04955	C04955	55 gal. (208 L)	Drum	1	400 lbs.

PROPERTIES

Appearance/physical state	Gas/Aerosol
Odor	Mild Orange
Melting point/freezing point	Not established
Boiling point/range	314.6°F (157°C)
Vapor pressure	2 mm Hg @20°C
Partition coefficient	<1
Percent volatile	100%
Flammability limit	Flammability limit - lower (%) 0.7% Flammability limit - upper (%) 6%
Propellant	Petroleum Gases, Liquefied
VOC Content	(Aerosol) 97.2%, (Bulk) 100% per US State and Federal Consumer Product Regulations
Color	Clear water-white
Flash point	104.0°F (40.0°C) Tag Closed Cup (dispensed liquid)
Relative density	Not available
Evaporation rate	0.2 (BuAc = 1)
Vapor density	4.8 - 5.3
Auto-ignition temperature	> 442.4°F (> 228°C)
Viscosity	< 3 cSt
Specific Gravity (water=1)	0.77 - 0.79 @20°C
Temperature Range °F(°C)	Not available
4-Ball Weld Load	Not applicable

DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

HANDLING

Aerosol - Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. (see Section 7 of the SDS)

STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. (see Section 7 of the SDS)

DISPOSAL INFORMATION

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.lpslabs.com

©2018 ITW Pro Brands • LPS® is a registered trademark of Illinois Tool Works All Rights Reserved • TDS04920 • 180605