



Foodlube Chain Spray

Synthetic Lubricant



FEATURES

- Fully synthetic formula extends chain life, protecting vital assets and lowering maintenance costs.
- Exhibits excellent penetration and load carrying properties ensuring that the product lubricates and protects inside rollers, links, pins, etc.
- Provides a water displacing, strong bonding film with excellent water washout resistance and corrosion protection.
- Excellent oxidation stability reduces relubrication intervals and saves on lubricant usage.
- Powerful foaming action penetrates close tolerances of chain bushings and pins.
- NSF® Registered H1 #147490
- Features DETEX® metal & x-ray detectable plastic components

APPLICATIONS

- Bushings
- Casters
- Chains
- Cranes
- Drives
- Rollers
- Linkage
- Pins
- Pulleys

SPECIFICATIONS AND APPROVALS

- FOODLUBE Chain Spray is manufactured from only FDA listed ingredients: FDA Group 21 CFR 178.3570
- CARB Compliant
- NSF® H1 Registration # 147490
- No VOCs

IS (IDENTIFICATION SYSTEM)



AVAILABLE PRODUCTS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
57616	N/A	11 wt. oz./312 g/422 mL	Aerosol	12	11 lbs.

PROPERTIES

Appearance/physical state	Liquid
Odor	Mild
Melting point/freezing point	Not established
Boiling point/range	Not established
Vapor pressure	> 200 mm Hg @ 20°C
Partition coefficient	> 1
Percent volatile	20 - 30%
Flammability limit	Lower: 1.8%, Upper: 7.0%
Propellant	Propane
VOC Content	24% per US State & Federal Consumer Product Regulations
Color	Clear, colorless
Flash point	-118°C (-180°F) - propellant
Relative density	Not established
Evaporation rate	1
Vapor density	>1
Auto-ignition temperature	> 200°C (392°F)
Viscosity	150 mm ² /s (cSt) @ 40°C
Specific Gravity (water=1)	0.85
Temperature Range °F(°C)	Not established
4-Ball Weld Load	Not established

DIRECTIONS

Hold can 8 to 12 inches (20 to 30 cm) away from surface to be sprayed. Spray light, even coat. Use at room temperature 70°F (21°C) for best results. Product should be sprayed in a well ventilated area. Repeat application if necessary.

HANDLING

DO NOT spray into or around ignition sources. After handling, always wash hands thoroughly with soap and water. Use only with adequate ventilation. Avoid breathing vapors or spray mists.

STORAGE

Keep container closed and in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F (49°C).

DISPOSAL INFORMATION

Dispose of contents/container in accordance with local / regional / national regulations. [P501]



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.lpslabs.com

©2018 ITW Pro Brands • LPS® is a registered trademark of Illinois Tool Works All Rights Reserved • TDS57616 • 180605

LUBRICANTS/PENETRANTS