



Foodlube Sugar Dissolving Fluid



FEATURES

- Rapidly dissolves and removes sugars and fondants from applications commonly found in food and beverage facilities.
- Leaves a light, durable lubricating film on the surface to prevent new accumulations of sugar.
- Provides short term corrosion protection on exposed metal surfaces.
- FOODLUBE Sugar Dissolving Fluid offers a wide temperature resistance of 41°F to 203°F (+5°C to +95°C).
- NSF® Registered H1 #147495 (aerosol); #147492 (bulk)
- Features DETEX® metal & x-ray detectable plastic components

APPLICATIONS

- Animal feed sugar residue
- Chains on flow wrapping equipment
- Conveyors
- Cutters or blades
- Sugar build-up on fasteners
- Sugar packaging lines
- Sugar processing lines
- Weighting plates

SPECIFICATIONS AND APPROVALS

- FOODLUBE Sugar Dissolving Fluid is manufactured from only FDA listed ingredients: FDA Group 21 CFR 178.3570
- NSF® H1 Registration # 147495 (aerosol); # 147492 (bulk)

IS (IDENTIFICATION SYSTEM)



AVAILABLE PRODUCTS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
57716	N/A	15 wt. oz./425 g/427 mL	Aerosol	12	18 lbs.
57728	N/A	28 fl. oz. (828 mL)	Trigger Spray	12	27 lbs.
57701	N/A	1 gal. (3.78 L)	Bottles	4	38 lbs.

PROPERTIES

Appearance/physical state	Liquid
Odor	Mild
Melting point/freezing point	Not available.
Boiling point/range	212 °F (> 100 °C)
Vapor pressure	Aerosol: <1.00 mm Hg @ 20°C, Bulk: ~ 18 mmHg @ 20°C
Partition coefficient	<1
Percent volatile	80%
Flammability limit	Not available.
Propellant	Aerosol: Propane, Bulk: N/A
VOC Content	Aerosol: 4% Bulk: 0% per US State & Federal Consumer Product Regulations
Color	Colorless
Flash point	Aerosol: -118°C (-180°F) TCC propellant Bulk: >302°F (> 150°C)
Relative density	Not available.
Evaporation rate	1
Vapor density	>1
Auto-ignition temperature	Not available
Viscosity	Not available
Specific Gravity (water=1)	1 - 1.1 @ 20°C
Temperature Range °F(°C)	41°F to 203°F
4-Ball Weld Load	Not available

DIRECTIONS

Aerosol: Shake container thoroughly before use. Hold can 8 to 12 inches (20 to 30 cm) away from surface to be sprayed. Spray light, even coat. Use at room temperature 70°F (21°C) for best results. Product should be sprayed in a well ventilated area. Repeat application if necessary. Bulk: MIX WELL. Protect from freezing. If frozen, allow to return to room temperature and mix well. Turn nozzle to spray or stream position. Pull trigger to spray. Suitable for application directly onto the surface to be cleaned. Can be applied directly from the hand trigger pack or by spraying, dipping, brush, or oil can.

HANDLING

Aerosol: DO NOT spray into or around ignition sources. After handling, always wash hands thoroughly with soap and water. Use only with adequate ventilation. Avoid breathing vapors or spray mists. Bulk: Avoid prolonged exposure. Observe good industrial hygiene practices.

STORAGE

Aerosol: Keep container closed and in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F (49°C). Bulk: Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL INFORMATION

Aerosol: Dispose of contents/container in accordance with local / regional / national regulations.; Bulk: Dispose of waste and residues in accordance with local authority requirements.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.lpslabs.com

©2018 ITW Pro Brands • LPS® is a registered trademark of Illinois Tool Works All Rights Reserved • TDS57716 • 180605