



# G-49

# ORANGE DEGREASER LOW VOCS



## FEATURES

- Reduced VOCs (Volatile Organic Compounds)
- Conforms to the VOC regulations of CARB (California Air Resources Board), OTC (Ozone Transport Commission) and LADCO (Lake Michigan Air Directors Consortium)
- Instant cleaning action, no residue
- Excellent for removing grease, grime, oil, and adhesives
- High solvent strength
- Moderate evaporation
- Excellent alternative to Methyl Ethyl Ketone (MEK)
- Not a Hazardous Air Pollutant (HAP)
- No ozone depleting compounds (ODC)
- Inverta SprayValve can be sprayed at almost any angle
- NSF® registered category code C1, registration #142147

## APPLICATIONS

- Bearings
- Chains
- Controls
- De-energized Cable Connections
- Forklifts
- Gears
- Hand & Power Tools
- Heavy Equipment
- Instruments
- Machinery
- Motors
- Pulleys

## SPECIFICATIONS AND APPROVALS

- NSF® registered category code C1, registration #142147

### IS (IDENTIFICATION SYSTEM)



## AVAILABLE PRODUCTS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
06420	C06420	15 wt. oz./425 g/528 mL	Aerosol	12	15 lbs.

## PROPERTIES

Appearance/physical state	Gas/Aerosol
Odor	Acetone/Orange
Melting point/freezing point	Not established
Boiling point/range	Not established
Vapor pressure	Not established
Partition coefficient	Not established
Percent volatile	100%
Flammability limit	Flammability limit - lower (%) 2.5% Flammability limit - upper (%) 12.8%
Propellant	Carbon dioxide
VOC Content	9.45% per US State and Federal Consumer Product Regulations
Color	Clear water-white
Flash point	-4.0°F (-20.0°C) Tag Closed Cup (estimated)
Relative density	Not available
Evaporation rate	0.2 BuAc
Vapor density	Not established
Auto-ignition temperature	Not established
Viscosity	Not available
Specific Gravity (water=1)	0.81 @ 20°C
Temperature Range °F(°C)	Not applicable
4-Ball Weld Load	Not applicable

## DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

## HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. (See Section 7 of the SDS)

## STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat and sources of ignition. (See Section 7 of the SDS)

## DISPOSAL INFORMATION

Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.lpslabs.com](http://www.lpslabs.com)

©2018 ITW Pro Brands • LPS® is a registered trademark and G-49™ is a trademark of Illinois Tool Works All Rights Reserved • TDS06420 • 180605

**INDUSTRIAL DEGREASERS**