

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name or designation of the mixture	LPS® 2 (Aerosol)
Registration number	-
Synonyms	None.
Part Number	00216, M00216
Issue date	20-September-2017
Version number	04
Revision date	03-January-2019
Supersedes date	23-August-2018

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	An industrial lubricant designed to displace moisture from equipment, provide heavy-duty lubrication and rust prevention.
Uses advised against	None known.

### 1.3. Details of the supplier of the safety data sheet

Supplier	Alsco Ltd
Company name	Unite 13 Hillmead Industrial Estate
Address	Marshall Road Swindon, Wiltshire United Kingdom SN5 5FZ
Telephone	+44 1793 733 900
In Case of Emergency	+001 703-527-3887
Manufacturer	
Company name	Rocol
Address	Rocol House Swillington Leeds LS26 8BS United Kingdom Tel: +44 (0) 113 232 2700 Fax: +44 (0) 113 232 2740
e-mail	lpssds@itwprobrands.com

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards		
Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.

**Hazard summary** Combustible. Aerosol CONTENTS UNDER PRESSURE.  
Pressurised container may explode when exposed to heat or flame.

### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

Contains:	Benzotriazole, Carbon dioxide, Distillates Petroleum Hydrotreated Light, Petroleum Oil
Hazard pictograms	



**Signal word** Danger  
**Hazard statements**  
H222 Extremely flammable aerosol.  
H229 Pressurized container: May burst if heated.

### Precautionary statements

#### Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.

#### Response

Wash hands after handling.

#### Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

#### Disposal

Dispose of waste and residues in accordance with local authority requirements.

### Supplemental label information

EUH066 - Repeated exposure may cause skin dryness or cracking.  
EUH208 - Contains Benzotriazole derivative. May produce an allergic reaction.

### 2.3. Other hazards

Not a PBT or vPvB substance or mixture. Combustible.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates Petroleum Hydrotreated Light	70 - 80	64742-47-8 265-149-8	01-2119456620-43-XXXX	649-422-00-2	
<b>Classification:</b>	Asp. Tox. 1;H304				
Petroleum Oil	10 - 20	64742-52-5 265-155-0	01-2119467170-45-XXXX	649-465-00-7	Note L
<b>Classification:</b>	Asp. Tox. 1;H304, Carc. 1B;H350				L
Carbon dioxide	1 - 5	124-38-9 204-696-9	-	-	#
<b>Classification:</b>	-				
Benzotriazole	≤ 0,1	95-14-7	-	-	
<b>Classification:</b>	Skin Irrit. 2;H315, Skin Sens. 1;H317, Aquatic Chronic 2;H411				

#### List of abbreviations and symbols that may be used above

DSD: Directive 67/548/EEC.  
CLP: Regulation No. 1272/2008.  
#: This substance has been assigned Union workplace exposure limit(s).  
M: M-factor  
PBT: persistent, bioaccumulative and toxic substance.  
vPvB: very persistent and very bioaccumulative substance.  
All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Note L: This component has been tested by Supplier. According to Supplier, the component complies with the criteria of Note L in Annex I of 67/548/EEC, and is exempt from a classification of T; R45. (Contains less than 3% DMSO)

**Composition comments** The full text for all R- and H-phrases is displayed in section 16.

## SECTION 4: First aid measures

#### General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 4.1. Description of first aid measures

**Inhalation** If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.  
**Skin contact** Wash off with soap and water. Get medical attention if irritation develops and persists.  
**Eye contact** Rinse with water. Get medical attention if irritation develops and persists.  
**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

#### 4.2. Most important symptoms and effects, both acute and delayed

Exposure may cause temporary irritation, redness, or discomfort.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

<b>General fire hazards</b>	Extremely flammable aerosol. Combustible.
<b>5.1. Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>5.2. Special hazards arising from the substance or mixture</b>	Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>5.3. Advice for firefighters</b>	
<b>Special protective equipment for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Special fire fighting procedures</b>	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

## SECTION 6: Accidental release measures

<b>6.1. Personal precautions, protective equipment and emergency procedures</b>	
<b>For non-emergency personnel</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.
<b>For emergency responders</b>	Keep unnecessary personnel away.
<b>6.2. Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.
<b>6.3. Methods and material for containment and cleaning up</b>	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapours or divert vapour cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material.
<b>6.4. Reference to other sections</b>	Not available.

## SECTION 7: Handling and storage

<b>7.1. Precautions for safe handling</b>	Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
<b>7.2. Conditions for safe storage, including any incompatibilities</b>	Level 3 Aerosol.  Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Level 3 Aerosol.
<b>7.3. Specific end use(s)</b>	Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	Ceiling	18000 mg/m <sup>3</sup>
		10000 ppm
	MAK	9000 mg/m <sup>3</sup> 5000 ppm

**Belgium. Exposure Limit Values.**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	54784 mg/m <sup>3</sup>
		30000 ppm
	TWA	9131 mg/m <sup>3</sup> 5000 ppm

**Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	MAC	9000 mg/m <sup>3</sup>
		5000 ppm

**Czech Republic. OELs. Government Decree 361**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	Ceiling	45000 mg/m <sup>3</sup>
	TWA	9000 mg/m <sup>3</sup>

**Denmark. Exposure Limit Values**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m <sup>3</sup>
		5000 ppm

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Finland. Workplace Exposure Limits**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m <sup>3</sup>
		5000 ppm

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	VME	9000 mg/m <sup>3</sup>
		5000 ppm
<b>Regulatory status:</b>	Regulatory indicative (VRI)	
<b>Regulatory status:</b>	Regulatory indicative (VRI)	

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

Components	Type	Value	Form
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m <sup>3</sup>	
		5000 ppm	
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	TWA	5 mg/m <sup>3</sup>	Respirable aerosol fraction
		350 mg/m <sup>3</sup>	Vapour.

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

Components	Type	Value	Form
		50 ppm	Vapour.

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	AGW	9100 mg/m <sup>3</sup>
		5000 ppm

**Greece. OELs (Decree No. 90/1999, as amended)**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m <sup>3</sup>
		5000 ppm
	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Hungary. OELs. Joint Decree on Chemical Safety of Workplaces**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Ireland. Occupational Exposure Limits**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	27000 mg/m <sup>3</sup>
		15000 ppm
	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Italy. Occupational Exposure Limits**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Latvia. OELs. Occupational exposure limit values of chemical substances in work environment**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Netherlands. OELs (binding)**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>

**Norway. Administrative Norms for Contaminants in the Workplace**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m <sup>3</sup>
		5000 ppm

**Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	STEL	27000 mg/m <sup>3</sup>
	TWA	9000 mg/m <sup>3</sup>

**Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm

**Spain. Occupational Exposure Limits**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Carbon dioxide (CAS 124-38-9)	TWA	9150 mg/m <sup>3</sup>
		5000 ppm

**Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	18000 mg/m3
		10000 ppm
	TWA	9000 mg/m3 5000 ppm

**Switzerland. SUVA Grenzwerte am Arbeitsplatz**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	STEL	700 mg/m3
	TWA	350 mg/m3

**UK. EH40 Workplace Exposure Limits (WELs)**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	27400 mg/m3
		15000 ppm
	TWA	9150 mg/m3 5000 ppm

**EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no effect levels (DNELs)** Not available.

**Predicted no effect concentrations (PNECs)** Not available.

**8.2. Exposure controls**

**Appropriate engineering controls** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**General information** Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

- **Hand protection** Wear appropriate chemical resistant gloves.

- **Other** Wear suitable protective clothing.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**Hygiene measures** When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**Environmental exposure controls** Environmental manager must be informed of all major releases.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Physical state	Gas.
Form	Aerosol
Colour	Brown.
Odour	Slight petroleum odor. Cherry.
Odour threshold	Not established
pH	Not applicable
Melting point/freezing point	< -50 °C (< -58 °F)
Initial boiling point and boiling range	195 °C (383 °F) @ 101 kPa
Flash point	79,0 °C (174,2 °F) Tag closed cup (dispensed liquid)
Evaporation rate	< 0,1 BuAc
Flammability (solid, gas)	Flammable gas.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0,6 %
Flammability limit - upper (%)	7 %
Vapour pressure	< 0,05 mm Hg @ 20°C (dispensed liquid)
Vapour density	4,7 (Air = 1)
Relative density	Not available.
Solubility(ies)	
Solubility (water)	< 3 %
Partition coefficient (n-octanol/water)	< 1
Auto-ignition temperature	> 228 °C (> 442,4 °F)
Decomposition temperature	Not established
Viscosity	< 7 cSt
Viscosity temperature	25 °C (77 °F)
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

#### 9.2. Other information

Heat of combustion	> 30 kJ/g
Percent volatile	92 - 95 %
Specific gravity	0,82 - 0,86 @ 20°C

## SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Carbon oxides.

## SECTION 11: Toxicological information

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

#### Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.



**Symptoms** Exposure may cause temporary irritation, redness, or discomfort.

### 11.1. Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

Components	Species	Test Results
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
Petroleum Oil (CAS 64742-52-5)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 3,9 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 2000 mg/kg
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.	
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.	
<b>Respiratory sensitisation</b>	Not a respiratory sensitizer.	
<b>Skin sensitisation</b>	This product is not expected to cause skin sensitisation.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
<b>Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)</b>		
Petroleum Oil (CAS 64742-52-5)		
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.	
<b>Specific target organ toxicity - single exposure</b>	Not classified.	
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.	
<b>Aspiration hazard</b>	Not likely, due to the form of the product.	
<b>Mixture versus substance information</b>	No information available.	
<b>Other information</b>	None known.	

## SECTION 12: Ecological information

**12.1. Toxicity** Based on available data, the classification criteria are not met for hazardous to the aquatic environment, acute hazard. Due to partial or complete lack of data the classification for hazardous to the aquatic environment, long term hazard, is not possible.

Components	Species	Test Results
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)		
<b>Aquatic</b>		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)
		2,9 mg/l, 96 hours

**12.2. Persistence and degradability**

**12.3. Bioaccumulative potential**

**Partition coefficient n-octanol/water (log Kow)**

LPS® 2 (Aerosol) < 1

**Bioconcentration factor (BCF)** Not available.

**12.4. Mobility in soil** No data available.

**12.5. Results of PBT and vPvB assessment** Not a PBT or vPvB substance or mixture.

**12.6. Other adverse effects** None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Residual waste** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

**EU waste code** The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Disposal methods/information** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Special precautions** Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

**14.1. UN number** UN1950

**14.2. UN proper shipping name** Aerosols, flammable

**14.3. Transport hazard class(es)**

- Class** 2.1
- Subsidiary risk** -
- Label(s)** 2.1
- Hazard No. (ADR)** Not available.
- Tunnel restriction code** D

**14.4. Packing group** Not available.

**14.5. Environmental hazards** No.

**14.6. Special precautions for user** Not available.

### RID

**14.1. UN number** UN1950

**14.2. UN proper shipping name** Aerosols, flammable

**14.3. Transport hazard class(es)**

- Class** 2.1
- Subsidiary risk** -
- Label(s)** 2.1

**14.4. Packing group** Not available.

**14.5. Environmental hazards** No.

**14.6. Special precautions for user** Not available.

### ADN

**14.1. UN number** UN1950

**14.2. UN proper shipping name** Aerosols, flammable

**14.3. Transport hazard class(es)**

- Class** 2.1
- Subsidiary risk** -
- Label(s)** 2.1

**14.4. Packing group** Not available.

**14.5. Environmental hazards** No.

**14.6. Special precautions for user** Not available.

### IATA

**14.1. UN number** UN1950

**14.2. UN proper shipping name** Aerosols, flammable

**14.3. Transport hazard class(es)**

- Class** 2.1
- Subsidiary risk** -

<b>Label(s)</b>	2.1
<b>14.4. Packing group</b>	Not available.
<b>14.5. Environmental hazards</b>	No.
<b>ERG Code</b>	10L
<b>14.6. Special precautions for user</b>	Not available.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.

#### IMDG

<b>14.1. UN number</b>	UN1950
<b>14.2. UN proper shipping name</b>	AEROSOLS, flammable
<b>14.3. Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>14.4. Packing group</b>	Not available.
<b>14.5. Environmental hazards</b>	
<b>Marine pollutant</b>	No
<b>EmS</b>	Not available.
<b>14.6. Special precautions for user</b>	Not available.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

ADN; ADR; IATA; IMDG; RID



## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

**EU Regulation 648/2004, Annex VII, Content Labeling for Detergents**

Not listed

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**

Not listed.

**Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

Carbon dioxide (CAS 124-38-9)

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

#### Authorisations

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

**Restrictions on use**

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

Petroleum Oil (CAS 64742-52-5)

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**

Petroleum Oil (CAS 64742-52-5)

**Other EU regulations**

**Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended**

Not listed.

**Other regulations**

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

**National regulations**

Follow national regulation for work with chemical agents.

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information**

**List of abbreviations**

Not available.

**References**

Not available.

**Information on evaluation method leading to the classification of mixture**

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

**Full text of any H-statements not written out in full under Sections 2 to 15**

H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H350 May cause cancer.  
H411 Toxic to aquatic life with long lasting effects.

**Revision information**

SECTION 2: Hazards identification: Supplemental label information

**Training information**

Follow training instructions when handling this material.

**Disclaimer**

Rocol cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.