



SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture LPS® Food Grade Electronic Cleaner
Registration number -
Synonyms None.
Part Number 58116, M58116
Issue date 15-November-2016
Version number 01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses A spray cleaner designed to remove dirt, moisture, dust, flux or oxides from the internal components of electronic or precision equipment such as circuit boards.
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Supplier AlSCO Ltd
Company name Unit 13 Hillmead Industrial Estate
Address Marshall Road
Swindon, Wiltshire
United Kingdom SN5 5FZ
Telephone +44 1793 733 900
In Case of Emergency +001 703-527-3887
Manufacturer
Company name ITW Pro Brands
Address 4647 Hugh Howell Rd., Tucker, GA 30084 (U.S.A.)
Website <http://www.lpslabs.com>
e-mail lpssds@itwprobrands.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification R10, Xn;R48/20, Xi;R38, R67, N;R51/53

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols	Category 2	H223 - Flammable aerosol. H229 - Pressurized container: May burst if heated.
----------	------------	---

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Reproductive toxicity	Category 2	H361 - Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (inhalation)	Category 2 (nervous system)	H373 - May cause damage to organs (nervous system) through prolonged or repeated exposure by inhalation.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 2	H411 - Toxic to aquatic life with long lasting effects.
--	------------	---

Hazard summary

Physical hazards	Flammable.
Health hazards	May impair fertility. May cause harm to the unborn child. Irritating to skin. Also harmful: danger of serious damage to health by prolonged exposure through inhalation. Vapours may cause drowsiness and dizziness. Occupational exposure to the substance or mixture may cause adverse health effects.
Environmental hazards	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Specific hazards	None known.
Main symptoms	May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioural changes. Decrease in motor functions. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Ethane, 1,1,1,2-tetrafluoro-(hfc-134a), Isopropanol, Naphtha (petroleum), hydrotreated light, n-Hexane, Pentane

Hazard pictograms



Signal word

Warning

Hazard statements

H223	Flammable aerosol.
H229	Pressurized container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs (nervous system) through prolonged or repeated exposure by inhalation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe gas.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response

P302 + P352	IF ON SKIN: Wash with plenty of water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor if you feel unwell.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.

Storage

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Supplemental label information None known.

2.3. Other hazards None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Naphtha (petroleum), hydrotreated light	60 - 70	64742-49-0 265-151-9	-	649-328-00-1	
Classification:		DSD: Carc. Cat. 2;R45, Muta. Cat. 2;R46, Xn;R65			P
		CLP: Flam. Liq. 2;H225, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Muta. 1B;H340, Carc. 1B;H350, Repr. 2;H361, Aquatic Chronic 2;H411			P
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a)	20 - 30	811-97-2 212-377-0	-	-	
Classification:		DSD: -			
		CLP: -			
Isopropanol	1 - 10	67-63-0 200-661-7	-	603-117-00-0	
Classification:		DSD: F;R11, Xi;R36, R67			
		CLP: Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336			
n-Hexane	1 - 2	110-54-3 203-777-6	-	601-037-00-0	#
Classification:		DSD: F;R11, Repr. Cat. 3;R62, Xn;R65-48/20, Xi;R38, R67, N;R51/53			
		CLP: Flam. Liq. 2;H225, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, STOT RE 2;H373, Aquatic Chronic 2;H411			
Pentane	1 - 2	109-66-0 203-692-4	-	601-006-00-1	#
Classification:		DSD: F+;R12, Xn;R65, R66-67, N;R51/53			C
		CLP: Flam. Liq. 2;H225, Asp. Tox. 1;H304, STOT SE 3;H336, Aquatic Chronic 2;H411			C

List of abbreviations and symbols that may be used above

DSD: Directive 67/548/EEC.

CLP: Regulation No. 1272/2008.

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note P: The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7).

Composition comments The full text for all R- and H-phrases is displayed in section 16.

SECTION 4: First aid measures**General information**

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

4.1. Description of first aid measures**Inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioural changes. Decrease in motor functions. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing media Not available.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections Use personal protection recommended in Section 8 of the SDS. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities Store locked up. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits**Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001**

Components	Type	Value
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2)	MAK	4200 mg/m3
	STEL	1000 ppm 16800 mg/m3
Isopropanol (CAS 67-63-0)	MAK	4000 ppm 500 mg/m3
	STEL	200 ppm 2000 mg/m3
n-Hexane (CAS 110-54-3)	MAK	800 ppm 72 mg/m3
	STEL	20 ppm 288 mg/m3
Pentane (CAS 109-66-0)	Ceiling	80 ppm 3600 mg/m3
	MAK	1200 ppm 1800 mg/m3
		600 ppm

Belgium. Exposure Limit Values.

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3
	TWA	400 ppm 500 mg/m3
n-Hexane (CAS 110-54-3)	TWA	200 ppm 72 mg/m3
		20 ppm
Pentane (CAS 109-66-0)	STEL	2250 mg/m3
	TWA	750 ppm 1800 mg/m3
		600 ppm

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3
	TWA	980 mg/m3
n-Hexane (CAS 110-54-3)	TWA	72 mg/m3
		20 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3
		1000 ppm

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2)	MAC	4240 mg/m3
		1000 ppm
Isopropanol (CAS 67-63-0)	MAC	999 mg/m3
	STEL	400 ppm 1250 mg/m3
n-Hexane (CAS 110-54-3)	MAC	500 ppm 72 mg/m3
		20 ppm
Pentane (CAS 109-66-0)	MAC	3000 mg/m3
		1000 ppm

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Type	Value
Isopropanol (CAS 67-63-0)	TWA	980 mg/m3
		400 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value
Isopropanol (CAS 67-63-0)	Ceiling	1000 mg/m3
	TWA	500 mg/m3
n-Hexane (CAS 110-54-3)	Ceiling	200 mg/m3
	TWA	70 mg/m3
Pentane (CAS 109-66-0)	Ceiling	4500 mg/m3
	TWA	3000 mg/m3

Denmark. Exposure Limit Values

Components	Type	Value
Isopropanol (CAS 67-63-0)	TLV	490 mg/m3
		200 ppm
n-Hexane (CAS 110-54-3)	TLV	72 mg/m3
		20 ppm
Pentane (CAS 109-66-0)	TLV	1500 mg/m3
		500 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	600 mg/m3
		250 ppm
		TWA
n-Hexane (CAS 110-54-3)	TWA	350 mg/m3
		150 ppm
		72 mg/m3
Pentane (CAS 109-66-0)	TWA	20 ppm
		3000 mg/m3
		1000 ppm

Finland. Workplace Exposure Limits

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	620 mg/m3
		250 ppm
		TWA
n-Hexane (CAS 110-54-3)	STEL	500 mg/m3
		200 ppm
		2300 mg/m3
Pentane (CAS 109-66-0)	STEL	630 ppm
		TWA
		72 mg/m3
Pentane (CAS 109-66-0)	TWA	20 ppm
		1900 mg/m3
		630 ppm
Pentane (CAS 109-66-0)	TWA	1500 mg/m3
		500 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value	Form	
Isopropanol (CAS 67-63-0)	VLE	980 mg/m3		
		400 ppm		
n-Hexane (CAS 110-54-3)	VLE	1500 mg/m3	Vapor.	
		VME		72 mg/m3
		20 ppm		
Pentane (CAS 109-66-0)	VME	3000 mg/m3		
		1000 ppm		

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2)	TWA	4200 mg/m3
		1000 ppm
Isopropanol (CAS 67-63-0)	TWA	500 mg/m3
		200 ppm
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3
		50 ppm

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value
Pentane (CAS 109-66-0)	TWA	3000 mg/m ³ 1000 ppm

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2)	AGW	4200 mg/m ³ 1000 ppm
Isopropanol (CAS 67-63-0)	AGW	500 mg/m ³ 200 ppm
n-Hexane (CAS 110-54-3)	AGW	180 mg/m ³ 50 ppm
Pentane (CAS 109-66-0)	AGW	3000 mg/m ³ 1000 ppm

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m ³ 500 ppm
	TWA	980 mg/m ³ 400 ppm
n-Hexane (CAS 110-54-3)	TWA	72 mg/m ³ 20 ppm

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	2000 mg/m ³
	TWA	500 mg/m ³
n-Hexane (CAS 110-54-3)	TWA	72 mg/m ³
Pentane (CAS 109-66-0)	TWA	2950 mg/m ³

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value
Isopropanol (CAS 67-63-0)	TWA	490 mg/m ³ 200 ppm
n-Hexane (CAS 110-54-3)	TWA	90 mg/m ³ 25 ppm
Pentane (CAS 109-66-0)	TWA	1500 mg/m ³ 500 ppm

Ireland. Occupational Exposure Limits

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
n-Hexane (CAS 110-54-3)	TWA	72 mg/m ³ 20 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m ³ 1000 ppm

Italy. Occupational Exposure Limits

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
n-Hexane (CAS 110-54-3)	TWA	72 mg/m ³ 20 ppm
Pentane (CAS 109-66-0)	TWA	2000 mg/m ³ 667 ppm

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	600 mg/m ³
	TWA	350 mg/m ³

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value
n-Hexane (CAS 110-54-3)	STEL	300 mg/m3
	TWA	72 mg/m3
		20 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3
		1000 ppm

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2)	STEL	3000 mg/m3
	TWA	750 ppm 2000 mg/m3
Isopropanol (CAS 67-63-0)	STEL	500 ppm 600 mg/m3
	TWA	250 ppm 350 mg/m3
n-Hexane (CAS 110-54-3)	TWA	150 ppm 72 mg/m3
		20 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3
		1000 ppm

Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A

Components	Type	Value
n-Hexane (CAS 110-54-3)	TWA	72 mg/m3
		20 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3
		1000 ppm

Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)

Components	Type	Value
n-Hexane (CAS 110-54-3)	TWA	72 mg/m3
		20 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3
		1000 ppm

Netherlands. OELs (binding)

Components	Type	Value
n-Hexane (CAS 110-54-3)	STEL	144 mg/m3
	TWA	72 mg/m3
Pentane (CAS 109-66-0)	TWA	1800 mg/m3

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value
Isopropanol (CAS 67-63-0)	TLV	245 mg/m3
		100 ppm
n-Hexane (CAS 110-54-3)	TLV	72 mg/m3
		20 ppm
Pentane (CAS 109-66-0)	TLV	750 mg/m3
		250 ppm

Poland. MACs. Regulation regarding maximum permissible concentrations and intensities of harmful factors in the work environment, Annex 1

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1200 mg/m3
	TWA	900 mg/m3
n-Hexane (CAS 110-54-3)	TWA	72 mg/m3
Pentane (CAS 109-66-0)	TWA	3000 mg/m3

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)

Components	Type	Value
n-Hexane (CAS 110-54-3)	TWA	72 mg/m3

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)

Components	Type	Value
Pentane (CAS 109-66-0)	TWA	20 ppm
		3000 mg/m3
		1000 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	400 ppm
		TWA
n-Hexane (CAS 110-54-3)	TWA	50 ppm
Pentane (CAS 109-66-0)	TWA	600 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value	
Isopropanol (CAS 67-63-0)	STEL	500 mg/m3	
		TWA	203 ppm
		TWA	200 mg/m3
n-Hexane (CAS 110-54-3)	TWA	81 ppm	
		TWA	72 mg/m3
		TWA	20 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3	
		TWA	1000 ppm

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value	
Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3	
		TWA	400 ppm
		TWA	500 mg/m3
n-Hexane (CAS 110-54-3)	STEL	200 ppm	
		TWA	140 mg/m3
		TWA	40 ppm
Pentane (CAS 109-66-0)	TWA	72 mg/m3	
		TWA	20 ppm
		TWA	3000 mg/m3
		1000 ppm	

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2)	TWA	4200 mg/m3
		TWA
Isopropanol (CAS 67-63-0)	TWA	500 mg/m3
		TWA
n-Hexane (CAS 110-54-3)	TWA	72 mg/m3
		TWA
Pentane (CAS 109-66-0)	TWA	3000 mg/m3
		TWA

Spain. Occupational Exposure Limits

Components	Type	Value	
Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3	
		TWA	400 ppm
		TWA	500 mg/m3
n-Hexane (CAS 110-54-3)	TWA	200 ppm	
		TWA	72 mg/m3
		TWA	20 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3	
		TWA	1000 ppm

Sweden. Occupational Exposure Limit Values

Components	Type	Value
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2)	STEL	3000 mg/m3

Sweden. Occupational Exposure Limit Values

Components	Type	Value
Isopropanol (CAS 67-63-0)	TWA	750 ppm 2000 mg/m3
	STEL	500 ppm 600 mg/m3
	TWA	250 ppm 350 mg/m3
	STEL	150 ppm 180 mg/m3
n-Hexane (CAS 110-54-3)	TWA	90 mg/m3
	STEL	25 ppm
	TWA	2000 mg/m3
Pentane (CAS 109-66-0)	STEL	750 ppm
	TWA	1800 mg/m3
	TWA	600 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2)	TWA	4200 mg/m3
Isopropanol (CAS 67-63-0)	STEL	1000 ppm 1000 mg/m3
	TWA	400 ppm 500 mg/m3
n-Hexane (CAS 110-54-3)	STEL	200 ppm 1440 mg/m3
	TWA	400 ppm 180 mg/m3
Pentane (CAS 109-66-0)	STEL	50 ppm 3600 mg/m3
	TWA	1200 ppm 1800 mg/m3
	TWA	600 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2)	TWA	4240 mg/m3
Isopropanol (CAS 67-63-0)	STEL	1000 ppm 1250 mg/m3
	TWA	500 ppm 999 mg/m3
n-Hexane (CAS 110-54-3)	TWA	400 ppm 72 mg/m3
Pentane (CAS 109-66-0)	TWA	20 ppm 1800 mg/m3
	TWA	600 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Type	Value
n-Hexane (CAS 110-54-3)	TWA	72 mg/m3 20 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m3
	TWA	1000 ppm

Biological limit values

Croatia. BLV. Dangerous Substance Exposure Limit Values at Workplace, Annexes 4 (as amended)

Components	Value	Determinant	Specimen	Sampling time
Isopropanol (CAS 67-63-0)	50 mg/l	Acetone	Urine	*
	50 mg/l	Acetone	Blood	*
n-Hexane (CAS 110-54-3)	150 µg/l	n-Hexane	Blood	*

Croatia. BLV. Dangerous Substance Exposure Limit Values at Workplace, Annexes 4 (as amended)

Components	Value	Determinant	Specimen	Sampling time
	5,3 mg/g	2,5-Hexanedione	Creatinine in urine	*
	5,25 mmol/mol	2,5-Hexanedione	Creatinine in urine	*
	40 ppm	n-Hexane	End-exhaled air	*
	1,74 umol/l	n-Hexane	Blood	*
	1,66 umol/l	n-Hexane	End-exhaled air	*

* - For sampling details, please see the source document.

France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 2065)

Components	Value	Determinant	Specimen	Sampling time
n-Hexane (CAS 110-54-3)	5 mg/g	2,5-Hexanedione	Creatinine in urine	*

* - For sampling details, please see the source document.

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling time
Isopropanol (CAS 67-63-0)	25 mg/l	Aceton	Urine	*
	25 mg/l	Aceton	Blood	*
n-Hexane (CAS 110-54-3)	5 mg/l	2,5-Hexanedione plus 4,5-Dihydroxy-2-hexanon (nach Hydrolyse)	Urine	*

* - For sampling details, please see the source document.

Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices

Components	Value	Determinant	Specimen	Sampling time
n-Hexane (CAS 110-54-3)	3,5 mg/g	hexane-2,5-dion	Creatinine in urine	*
	3,5 µmol/mmol	hexane-2,5-dion	Creatinine in urine	*

* - For sampling details, please see the source document.

Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2

Components	Value	Determinant	Specimen	Sampling time
n-Hexane (CAS 110-54-3)	3 mg/g	2,5-hexanedione and 4,5-dihydroxy-2-hexanon	Creatinine in urine	*
	5 mg/l	2,5-hexanedione and 4,5-dihydroxy-2-hexanon	Urine	*

* - For sampling details, please see the source document.

Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4

Components	Value	Determinant	Specimen	Sampling time
Isopropanol (CAS 67-63-0)	40 mg/l	Acetona	Urine	*
n-Hexane (CAS 110-54-3)	0,2 mg/l	2,5-Hexanedione, sin hidrólisis	Urine	*

* - For sampling details, please see the source document.

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Determinant	Specimen	Sampling time
Isopropanol (CAS 67-63-0)	25 mg/l	Aceton	Urine	*
	25 mg/l	Aceton	Blood	*

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Determinant	Specimen	Sampling time
n-Hexane (CAS 110-54-3)	5 mg/l	2,5-Hexandion plus 4,5-Dihydroxy-2-hexanon	Urine	*

* - For sampling details, please see the source document.

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs) Not available.

Predicted no effect concentrations (PNECs) Not available.

8.2. Exposure controls

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

- Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls Inform appropriate managerial or supervisory personnel of all environmental releases.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

Physical state Gas.
Form Aerosol
Colour Clear. Colourless.

Odour Hydrocarbon-like.

Odour threshold Not available.

pH Not applicable.

Melting point/freezing point Not available.

Initial boiling point and boiling range 58,33 °C (136,99 °F) Dispensed liquid.

Flash point < -17,0 °C (< 1,4 °F) Tag closed cup

Evaporation rate < 1 BuAc (Ethyl Ether = 1)

Flammability (solid, gas) Flammable gas.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Vapour pressure 352,53 mm Hg @ 38°C

Vapour density > 1 (Air = 1)

Relative density	Not available.
Solubility(ies)	
Solubility (water)	< 10 %
Solubility (other)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	< 3 cSt
Viscosity temperature	25 °C (77 °F)
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2. Other information	
Density	5,65
Heat of combustion	> 30 kJ/g
Percent volatile	100 %
Specific gravity	0,68
VOC	74 % per US State and Federal Consumer Product Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Contact with incompatible materials.
10.5. Incompatible materials	Acids. Strong oxidising agents. Isocyanates. Chlorine.
10.6. Hazardous decomposition products	Carbon oxides.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioural changes. Decrease in motor functions. Skin irritation. May cause redness and pain.

11.1. Information on toxicological effects

Acute toxicity

Components	Species	Test results
Isopropanol (CAS 67-63-0)		
Acute		
Dermal		
LD50	Rabbit	16,4 ml/kg, 24 Hours
Oral		
LD50	Rat	4,7 g/kg
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
Acute		
Dermal		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Oral		
LD50	Rat	> 2000 mg/kg

Components	Species	Test results
n-Hexane (CAS 110-54-3)		
Acute		
Dermal		
LD50	Rabbit	> 5 ml/kg, 4 Hours
Inhalation		
<i>Vapour</i>		
LC50	Rat	73860 ppm, 4 Hours
Oral		
LD50	Rat	49 ml/kg
Pentane (CAS 109-66-0)		
Acute		
Inhalation		
<i>Vapour</i>		
LC50	Rat	> 25,3 mg/l, 4 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory sensitisation	Not a respiratory sensitizer.	
Skin sensitisation	This product is not expected to cause skin sensitisation.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
ACGIH Carcinogens		
Isopropanol (CAS 67-63-0)	Not classifiable as a human carcinogen. A4	
Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)		
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
Reproductive toxicity	Suspected of damaging fertility or the unborn child.	
Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)		
n-Hexane (CAS 110-54-3)	Toxic for reproduction - category 2.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	May cause damage to organs (nervous system) through prolonged or repeated exposure by inhalation.	
Aspiration hazard	Not likely, due to the form of the product.	
Mixture versus substance information	No information available.	
Other information	Symptoms may be delayed.	

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life with long lasting effects. Based on available data, the classification criteria are not met for hazardous to the aquatic environment, acute hazard.

Components	Species	Test results
Isopropanol (CAS 67-63-0)		
Aquatic		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) > 1400 mg/l, 96 hours
n-Hexane (CAS 110-54-3)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 2,101 - 2,981 mg/l, 96 hours

12.2. Persistence and degradability No data is available on the degradability of this product.

12.3. Bioaccumulative potential

Partition coefficient**n-octanol/water (log Kow)**

Ethane, 1,1,1,2-tetrafluoro-(hfc-134a)	1,06
Isopropanol	0,05
n-Hexane	3,9
Pentane	3,39

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB assessment Not available.

12.6. Other adverse effects None known.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information**ADR**

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Hazard No. (ADR)	Not available.
Tunnel restriction code	Not available.
14.4. Packing group	Not applicable.
14.5. Environmental hazards	No
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
14.4. Packing group	Not applicable.
14.5. Environmental hazards	No
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1

- 14.4. **Packing group** Not applicable.
 14.5. **Environmental hazards** No
 14.6. **Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

IATA

- 14.1. **UN number** UN1950
 14.2. **UN proper shipping name** Aerosols, flammable
 14.3. **Transport hazard class(es)**
 Class 2.1
 Subsidiary risk -
 Label(s) 2.1
 14.4. **Packing group** Not applicable.
 14.5. **Environmental hazards** No
 14.6. **Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

IMDG

- 14.1. **UN number** UN1950
 14.2. **UN proper shipping name** Aerosols, flammable
 14.3. **Transport hazard class(es)**
 Class 2.1
 Subsidiary risk -
 Label(s) 2.1
 14.4. **Packing group** Not applicable.
 14.5. **Environmental hazards**
 Marine pollutant No
 EmS Not available.
 14.6. **Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

- 14.7. **Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

n-Hexane (CAS 110-54-3)

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Isopropanol (CAS 67-63-0)

n-Hexane (CAS 110-54-3)

Pentane (CAS 109-66-0)

Other regulations

Pregnant women should not work with the product, if there is the least risk of exposure. The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

Follow national regulation for work with chemical agents. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

Not available.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R10 Flammable.

R11 Highly flammable.

R12 Extremely flammable.

R36 Irritating to eyes.

R38 Irritating to skin.

R45 May cause cancer.

R46 May cause heritable genetic damage.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R60 May impair fertility.

R61 May cause harm to the unborn child.

R62 Possible risk of impaired fertility.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H340 May cause genetic defects.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Revision information

None.

Training information

Follow training instructions when handling this material.

Disclaimer

ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.