



# T-91 Non-Solvent Degreaser



## FEATURES

- Ideal for traditional solvent cleaning, plastic basin style part washers and dip tanks
- VOC compliant in all 50 states
- Zero VOCs: VOC's per CARB/OTC/ LADCO: 0 g/L, VOC content per SCAQMD: 0 g/L
- Biodegradable
- Efficient: requires less product than traditional solvents to get the job done
- pH = 8 - 9
- Contains no solvents
- Moderate foam for effective mechanical cleaning
- Nonfood Compounds Program Listed Category Code: A1 Registration #141975
- Acceptable for use in Canadian Food Processing Establishments

## APPLICATIONS

- Basin style parts washer
- Bilges
- Compressors
- Concrete
- Dip Tanks
- Drill presses
- Engines
- Floors
- Forklifts
- Grease traps
- Machinery
- Marine
- Tanks
- Tools

## SPECIFICATIONS AND APPROVALS

- NSF International
- Canadian Food Inspection Agency

### IS (IDENTIFICATION SYSTEM)



## AVAILABLE PRODUCTS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
06328	C06328	28 fl. oz. (828 mL)	Trigger	12	27 lbs.
06301	C06301	1 gal. (3.78 L)	Bottles	4	38 lbs.
06305	C06305	5 gal. (18.93 L)	Pail	1	45 lbs.
06355	C06355	55 gal. (208 L)	Drum	1	535 lbs.

## PROPERTIES

Appearance/physical state	Liquid
Odor	Mild soapy
Melting point/freezing point	Not available.
Boiling point/range	Not available
Vapor pressure	18 mm Hg
Partition coefficient	< 0
Percent volatile	85-87%
Flammability limit	Not established
Propellant	Not applicable
VOC Content	0% per State and Federal Consumer Product Regulations
Color	Colourless to light yellow
Flash point	None
Density	8.67 lb/gal
Evaporation rate	1 BuAc (Water = 1)
Vapor density	Not established
Auto-ignition temperature	Not established
Viscosity	Not established
Specific Gravity (water=1)	1.03
Temperature Range °F(°C)	Not applicable
4-Ball Weld Load	Not applicable
Solubility (water)	100%

## DIRECTIONS

(Trigger) Turn nozzle to spray or stream position. Pull trigger to spray. Then agitate surface with a brush cloth or wipe. Remove soils by wiping. Rinse with water for residue free surface. NOTE: Test for compatibility on sensitive materials. Do not heat above 175°F (79°C). Do not allow parts to soak longer than 24 hours.

**As a direct solvent degreaser replacement: Use T-91 undiluted (straight) as a direct solvent replacement for all heavy duty degreasing applications. Dilution Ratio Product: (as a neutral pH cleaner) Water**

Water	Applications: (Suggested dilution ranges for cleaning surfaces not damaged by water alone)
1:10 - 1:75	Floors: Light to Heavy Duty Cleaning/Degreasing
Undiluted to 1 : 10	Metals: Heavy Duty Cleaning/Degreasing
1:20 - 1:80	Plastics, rubbers & painted surfaces
1:50 - 1:100	Glass
1:10 - 1:80	Pressure Washing: Light to Heavy-Duty Cleaning/Degreasing
1:10 - 1:25	Soak Tanks [Do Not Exceed 140°F (60°C)]

## HANDLING

Observe good industrial hygiene practices

## STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## DISPOSAL INFORMATION

Waste from residues / unused products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Contaminated packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.lpslabs.com](http://www.lpslabs.com)

©2018 ITW Pro Brands • LPS® is a registered trademark and T-91™ is a trademark of Illinois Tool Works All Rights Reserved • TDS06328 • 180605